



SECOND & THIRD FLOOR ALTERNATE OFFICE CUBICLE AREA
 REFER TO THE ARCHITECTURAL PLANS FOR A PROPOSED "OPEN OFFICE" AREA LAYOUT ON THE THIRD FLOOR. PROVIDE APPROXIMATELY (20) TYPE "A2" 2X4 LIGHTS, (6) CEILING TYPE VACANCY SENSOR UNITS, (4) LOW VOLTAGE LIGHT SWITCHES, (18) QUADRAPLEX RECEPTACLES, (4) FLOOR FED FURNITURE POWER FEEDS, (4) FLOOR FED FURNITURE DATA FEEDS, (8) 4D DATA OUTLETS AND (2) FIRE ALARM AUDIO/VISUAL UNITS.





- TAGGED NOTES**
- L1 PROVIDE 120V/15 AMP POWER FROM RECEPTACLE CIRCUIT SERVING COUNTER TOP RECEPTACLES BELOW.
 - L13 ROUTE NUMBER OF #12 CONDUCTORS AND ONE (1) #12 GROUND AS INDICATED IN 3/4" CONDUIT TO NEAREST AVAILABLE NEW (SPARE 20A) BREAKERS IN EXISTING PANEL INDICATED. VERIFY EXACT PANEL LOCATION(S) AND BRANCH CIRCUITING PRIOR TO CONSTRUCTION. WHERE EXISTING PANEL IS FLUSH-MOUNTED IN AN EXISTING WALL TO REMAIN, CONTRACTOR SHALL CUT, PATCH, AND REPAIR WALL AS REQUIRED FOR CONCEALED CONDUIT ENTRY.
 - L14 PROVIDE FIXTURE TYPE "TL" LED TAPE LIGHTING AROUND FULL PERIMETER OF STAINED GLASS WINDOW. REFER TO LIGHT FIXTURE SCHEDULE FOR ADDITIONAL REQUIREMENTS AND INFORMATION.

- GENERAL NOTES (LIGHTING):**
- A. REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
 - B. CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER N.E.C. #310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER N.E.C. #300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN N.E.C #100 / 210.4 (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
 - C. ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES (LABEL INTERIOR OF BOX WHERE "IN WALL" SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT / CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
 - D. LOCATE CHAIN-HUNG INDUSTRIAL FIXTURES IN MECHANICAL ROOMS TO AVOID DUCTWORK AND PIPING. TO MAXIMIZE AVAILABLE LIGHT, SPACE AROUND EQUIPMENT, AIR HANDLERS, ETC. TO PROVIDE ADEQUATE LIGHTING TO ALL AREAS OF ROOM. PROVIDE ADDITIONAL FIXTURES OF SAME TYPE AS NEEDED TO FULFILL THIS REQUIREMENT.
 - E. LOCATE EXIT SIGNS FOR MAXIMUM VIEWING AREA. TO IDENTIFY EGRESS PATHS AS INDICATED ON PLANS. COORDINATE LOCATIONS SUCH THAT ARCHITECTURAL FEATURES OR EQUIPMENT FROM OTHER TRADES DO NOT OBSTRUCT VIEW.
 - F. WHERE EXIT SIGNS OR EMERGENCY BATTERY PACKS ARE PROVIDED, THEY SHALL BE CONNECTED TO AN UNSWITCHED LINE.
 - G. LUMINAIRES INDICATED WITH MULTILEVEL SWITCHING SHALL HAVE SIMILAR LAMPS CONTROLLED TOGETHER. I.E. INBOARD AND OUTBOARD LAMPS OR RIGHT AND LEFT HAND LAMPS.
 - H. ALL LIGHTING FIXTURE LENSES, PARABOLIC LOUVERS, DOWNLIGHTING ALZAK CONES AND "PARACUBE" LOUVERS SHALL BE HANDLED WITH COTTON GLOVES DURING INSTALLATION AND LAMPING TO AVOID FINGERPRINTS OR DIRT DEPOSITS. IT IS PREFERRED THAT FIXTURES BE SHIPPED AND INSTALLED WITH CLEAR PLASTIC BAGS TO PROTECT LOUVERS. AT CLOSE OF PROJECT, AND AFTER CONSTRUCTION AIR FILTERS ARE CHANGED, REMOVE BAGS. ANY LOUVER OR CONE SHOWING DIRT OR FINGER PRINTS SHALL BE CLEANED WITH SOLVENT RECOMMENDED BY THE MANUFACTURER, OR REPLACED AS NECESSARY IN ORDER TO TURN OVER TO THE OWNER NEW FIXTURES AT OCCUPANCY.
 - I. RECESSED LUMINAIRES SHALL BE SECURED SUCH THAT THE FORCE REQUIRED INSERTING LAMPS, TRIMS, LENSES, LOUVERS OR DOOR FRAMES DOES NOT SHIFT HOUSING. ALL TRIMS SHALL BE COMPLETELY FLUSH WITH FINISHED CEILINGS AT COMPLETION OF CONSTRUCTION. CONTRACTOR SHALL PROVIDE UNSWITCHED CONDUCTOR TO ALL EXIT SIGNS, EMERGENCY INVERTER BATTERY PACKS, AND NIGHT LIGHTS AS REQUIRED.
 - J.



1 SECOND FLOOR PLAN - LIGHTING
 SCALE: 1/8" = 1'-0"
 0 2 4 8 16 24 32'



KEYPLAN
 1" = 100'-0"

CONSULTANT Consultant: CMTA CONSULTING ENGINEERS, INC. 10411 MEETING STREET, PROSPECT, KY 40059 (502)326-3085 		ARCHITECT/ENGINEER OF RECORD A/E: GUIDON DESIGN, INC 1221 N PENNSYLVANIA STREET INDIANAPOLIS, IN 46202 (317) 800-6388 		STAMP 	Office of Construction and Facilities Management  U.S. Department of Veterans Affairs	Drawing Title SECOND FLOOR PLAN - LIGHTING Approved:	Phase BID DOCUMENTS	Project Title VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY	Project Number 589-701 Building Number 1 & 1C	Location WICHITA, KANSAS	Issue Date 05/22/2020	Checked PDY	Drawn RAH	Drawing Number ES201
---	--	--	--	--	---	---	-------------------------------	---	--	------------------------------------	---------------------------------	----------------	--------------	--------------------------------

SECOND & THIRD FLOOR ALTERNATE OFFICE CUBICLE AREA
 REFER TO THE ARCHITECTURAL PLANS FOR A PROPOSED "OPEN OFFICE" AREA LAYOUT ON THE THIRD FLOOR. PROVIDE APPROXIMATELY (20) TYPE "A2" 2X4 LIGHTS, (6) CEILING TYPE VACANCY SENSOR UNITS, (4) LOW VOLTAGE LIGHT SWITCHES, (18) QUADRAPLEX RECEPTACLES, (4) FLOOR FED FURNITURE POWER FEEDS, (4) FLOOR FED FURNITURE DATA FEEDS, (8) 4D DATA OUTLETS AND (2) FIRE ALARM AUDIO/VISUAL UNITS.

TAGGED NOTES
 L1 PROVIDE 120V/15 AMP POWER FROM RECEPTACLE CIRCUIT SERVING COUNTER TOP RECEPTACLES BELOW.
 L6 REFER TO ENLARGED PLAN OF PATIENT ROOM LIGHTING FOR TYPICAL CIRCUITING AND ADDITIONAL INFORMATION AND REQUIREMENTS.

- GENERAL NOTES (LIGHTING):**
- A. REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
 - B. CONTRACTOR SHALL FOLLOW LOW VOLTAGE CIRCUITING LAYOUT AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER N.E.C. #310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER N.E.C. #300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN N.E.C #100 / 210.4 (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
 - C. ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES (LABEL INTERIOR OF BOX WHERE "IN WALL" SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT / CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
 - D. LOCATE CHAIN-HUNG INDUSTRIAL FIXTURES IN MECHANICAL ROOMS TO AVOID DUCTWORK AND PIPING, TO MAXIMIZE AVAILABLE LIGHT. SPACE AROUND EQUIPMENT, AIR HANDLERS, ETC. TO PROVIDE ADEQUATE LIGHTING TO ALL AREAS OF ROOM. PROVIDE ADDITIONAL FIXTURES OF SAME TYPE AS NEEDED TO FULFILL THIS REQUIREMENT.
 - E. LOCATE EXIT SIGNS FOR MAXIMUM VIEWING AREA TO IDENTIFY EGRESS PATHS AS INDICATED ON PLANS. COORDINATE LOCATIONS SUCH THAT ARCHITECTURAL FEATURES OR EQUIPMENT FROM OTHER TRADES DO NOT OBSTRUCT VIEW.
 - F. WHERE EXIT SIGNS OR EMERGENCY BATTERY PACKS ARE PROVIDED, THEY SHALL BE CONNECTED TO AN UNSWITCHED LINE.
 - G. LUMINAIRES INDICATED WITH MULTILEVEL SWITCHING SHALL HAVE SIMILAR LAMPS CONTROLLED TOGETHER, I.E. INBOARD AND OUTBOARD LAMPS OR RIGHT AND LEFT HAND LAMPS.
 - H. ALL LIGHTING FIXTURE LENSES, PARABOLIC LOUVERS, DOWNLIGHTING ALZAK CONES AND "PARACUBE" LOUVERS SHALL BE HANDLED WITH COTTON GLOVES DURING INSTALLATION AND LAMPING TO AVOID FINGERPRINTS OR DIRT DEPOSITS. IT IS PREFERRED THAT FIXTURES BE SHIPPED AND INSTALLED WITH CLEAR PLASTIC BAGS TO PROTECT LOUVERS. AT CLOSE OF PROJECT, AND AFTER CONSTRUCTION AIR FILTERS ARE CHANGED, REMOVE BAGS. ANY LOUVER OR CONE SHOWING DIRT OR FINGER PRINTS SHALL BE CLEANED WITH SOLVENT RECOMMENDED BY THE MANUFACTURER, OR REPLACED AS NECESSARY IN ORDER TO TURN OVER TO THE OWNER NEW FIXTURES AT OCCUPANCY.
 - I. RECESSED LUMINAIRES SHALL BE SECURED SUCH THAT THE FORCE REQUIRED INSERTING LAMPS, TRIMS, LENSES, LOUVERS, OR DOOR FRAMES DOES NOT SHIFT HOUSING. ALL TRIMS SHALL BE COMPLETELY FLUSH WITH FINISHED CEILING AT COMPLETION OF CONSTRUCTION. CONTRACTOR SHALL PROVIDE UNSWITCHED CONDUCTOR TO ALL EXIT SIGNS, EMERGENCY INVERTER BATTERY PACKS, AND NIGHT LIGHTS AS REQUIRED.
 - J.



1 THIRD FLOOR PLAN - LIGHTING
 SCALE: 1/8" = 1'-0"
 0 2 4 8 16 24 32

KEYPLAN
 1" = 100'-0"

Revisions: Date:	CONSULTANT Consultant: CMTA CONSULTING ENGINEERS, INC. 10411 MEETING STREET, PROSPECT, KY 40059 (502)326-3085	ARCHITECT/ENGINEER OF RECORD A/E: GUIDON DESIGN, INC 1221 N PENNSYLVANIA STREET INDIANAPOLIS, IN 46202 (317) 800-6388	STAMP 	Office of Construction and Facilities Management VA U.S. Department of Veterans Affairs	Drawing Title THIRD FLOOR PLAN - LIGHTING Approved:	Phase BID DOCUMENTS	Project Title VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY	Project Number 589-701 Building Number 1 & 1C
	Location WICHITA, KANSAS	Issue Date 05/22/2020	Checked PDY	Drawn RAH	Drawing Number ES202			

ELEC - EQUIPMENT CONNECTION SCHEDULE


EQUIP ID	DISCONNECT MEANS	VOLTAGE	POLES	HP	POWER (KVA)	MCA
1-AC-1	E.C. PROVIDED DISCONNECT SWITCH	120	1		0.50	
1-AC-2	E.C. PROVIDED DISCONNECT SWITCH	120	1		0.50	
1-AHU-2	INTEGRAL CONTROL CABINET	480	3	4	0.50	81
1-CU-1	E.C. PROVIDED DISCONNECT SWITCH	208	2		0.50	
1-CU-2	E.C. PROVIDED DISCONNECT SWITCH	208	2		0.50	
1-EF-13	E.C. PROVIDED DISCONNECT SWITCH	120	1	0.25	0.50	2.85
1-F-HW4		208	3		0.50	
1-P-HWC-1		120	1		0.50	
1-REF-2	M.C. PROVIDED VFD	480	3	7.5	0.50	10
1-RTU-1 (RETURN)	E.C. PROVIDED DISCONNECT SWITCH	480	3	2.3	11.30	7
1-RTU-1 (SUPPLY)	E.C. PROVIDED DISCONNECT SWITCH	480	3	7	0.50	17
1EF-11		120	1		0.72	
1EF-12		120	1		1.26	
E-1-CRAC1	E.C. PROVIDED DISCONNECT SWITCH	480	3		8.00	12
E-1-CRAC2		480	3		13.30	20
E-1-CRAC3		480	3		13.30	20
E-1-CRAC4		480	3		8.00	12
E-1-EF1		208	3	2	2.20	
E-1-EH1		208	3	2	0.50	
E-1-IH1		208	3		0.50	
TEMP AHU (EXTERIOR)		480	3		1.00	

SECOND & THIRD FLOOR ALTERNATE OFFICE CUBICLE AREA



REFER TO THE ARCHITECTURAL PLANS FOR A PROPOSED "OPEN OFFICE" AREA LAYOUT ON THE THIRD FLOOR. PROVIDE APPROXIMATELY (20) TYPE "A2" 2X4 LIGHTS, (6) CEILING TYPE VACANCY SENSOR UNITS, (4) LOW VOLTAGE LIGHT SWITCHES, (18) QUADRAPLEX RECEPTACLES, (4) FLOOR FED FURNITURE POWER FEEDS, (4) FLOOR FED FURNITURE DATA FEEDS, (8) 4D DATA OUTLETS AND (2) FIRE ALARM AUDIOVISUAL UNITS.

TAGGED NOTES


- P1 PROPOSED LOCATION FOR TRANSFORMER DISCONNECT SWITCH AS INDICATED ON POWER RISER. REFER TO POWER RISER FOR SIZING AND EXACT REQUIREMENTS. LOCATE BESIDE TRANSFORMER IN ORDER TO MAINTAIN ALL REQUIRED CLEARANCES.
- P3 ROUTE ONE (1) #10 GROUND CONDUCTOR IN 1/2" CONDUIT CONTINUOUSLY AROUND ROOM (FULL CIRCLE) CONNECTING TO ALL PANELBOARD GROUND BARS IN ROOM AS REQUIRED BY N.E.C. 8517.14. CONTRACTOR SHALL ALSO SUBMIT DETAILED DIMENSIONED SHOP DRAWINGS OF ELECTRIC ROOMS INDICATING PANELBOARD, TRANSFORMER, DISCONNECT SWITCHES, ETC. LOCATIONS AND REQUIRED CLEARANCES.
- P9 COORDINATE OUTLET LOCATION WITH WALL PANELS IN AREA INDICATED SO THAT THE RECEPTACLE(S) IS CENTERED WITHIN INDIVIDUAL WALL PANELS. COORDINATE EXACT LOCATION AND MOUNTING WITH ARCHITECT AND ARCHITECT'S ELEVATIONS PRIOR TO ROUGH-IN.
- P11 ROUTE NUMBER OF #12 CONDUCTORS AND ONE (1) #12 GROUND AS INDICATED IN 3/4" CONDUIT TO NEAREST AVAILABLE NEW / SPARE 20A(1P BREAKER(S) IN EXISTING PANEL INDICATED. VERIFY EXACT PANEL LOCATIONS AND BRANCH CIRCUITING ROUTES PRIOR TO CONSTRUCTION. WHERE EXISTING PANEL IS FLUSH-MOUNTED IN AN EXISTING WALL TO REMAIN, CONTRACTOR SHALL CUT, PATCH, AND REPAIR WALL AS REQUIRED FOR CONCEALED CONDUIT ENTRY.
- P17 PROVIDE 4" CONCRETE HOUSEKEEPING PAD FOR EQUIPMENT INDICATED. CONFIRM ALL REQUIRED CLEARANCES FOR EQUIPMENT ARE MAINTAINED PRIOR TO POURING OF CONCRETE.
- P18 CONCEAL RECEPTACLE BEHIND ELECTRIC WATER COOLER (EWC), COORDINATE EXACT LOCATION WITH REMOTE, READILY ACCESSIBLE GFCI DEVICE NEXT TO EWC.
- P22 PROVIDE 120V/10 AMP POWER FROM RECEPTACLE CIRCUIT SERVING COUNTER TOP RECEPTACLES TO UNDERCABINET LIGHTING ABOVE.



2 ENLARGED 2ND FLOOR PLAN - ELEC C207




1 SECOND FLOOR PLAN - POWER



GENERAL NOTES (POWER):

- A. THIN SOLID LINES INDICATE EXISTING ITEMS TO REMAIN (U.O.N.) AND THICK SOLID LINES INDICATE NEW WORK.
- B. ALL NEW WIRING SHALL BE #12 WITH A #12 INSULATED GROUND WIRE (U.O.N.). CONDUIT SHALL BE 3/4" MINIMUM.
- C. REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
- D. CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RUN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.2(10) 210.4 (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
- E. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE CLEAR ADHESIVE LABELS WITH BLACK LETTERING. IN HEALTHCARE FACILITIES, ENGRAVE EMERGENCY DEVICE COVERPLATES IN PATIENT CARE AREAS. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
- F. RECEPTACLES THAT ARE CONTROLLED BY AN AUTOMATIC MEANS SUCH AS OCCUPANCY SENSOR OR ENERGY MANAGEMENT SYSTEM SHALL BE MARKED IN ACCORDANCE WITH NEC 408.3(E).
- G. LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.
- H. NO CONDUIT SHALL BE INSTALLED UNDERGROUND, EXCEPT FOR DISTRIBUTION EQUIPMENT FEEDERS, UNLESS REQUIRED FOR THE APPLICATION (FLOOR BOXES, ISLANDS, ETC.) OR SPECIFICALLY INDICATED AS SUCH IN CONSTRUCTION DOCUMENTS. NO CONDUIT SHALL BE INSTALLED WITHIN CONCRETE SLABS.
- I. ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES LABEL INTERIOR OF BOX WHERE "IN WALL" SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT / CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
- J. ALL CEILING MOUNTED DEVICES, FIXTURES, ETC. SHALL BE INSTALLED COMPLETELY FLUSH WITH FINISHED CEILING. CAREFULLY COORDINATE WITH DRYWALL CONTRACTOR TO ENSURE A FLUSH INSTALLATION. DRYWALL CONTRACTOR SHALL TAPE, MUD, AND SAND AS NEEDED. NO GAP BETWEEN DEVICE/FIXTURE AND CEILING WILL BE ACCEPTABLE. IF DEEMED THE ONLY SOLUTION BY THE ARCHITECT OR ENGINEER, THIS CONTRACTOR SHALL PROVIDE AN APPROVED SEALANT TO SEAL ANY SUCH GAPS THAT EXIST. A FINAL WALK-THROUGH SHALL BE SCHEDULED WITH THE OWNER TO APPROVE THE FINISHED CEILING CONDITION.
- K. NO CONDUIT, SUPPORTS, ETC. SHALL BE RUN THROUGH ACCESS CLEARANCES OF EQUIPMENT BY OTHER TRADES (I.E. VAV BOXES). COORDINATE WITH ALL TRADES PRIOR TO CONSTRUCTION.
- L. WHERE ANY RECEPTACLE IS LOCATED WITHIN 6'-0" OF SINK, CONTRACTOR SHALL PROVIDE "GFCI" TYPE OUTLET OR CONNECT CIRCUIT TO A 20A(1P GFCI TYPE CIRCUIT BREAKER. REFER TO ARCHITECTURAL PLANS FOR SINK LOCATIONS.
- M. PROVIDE COORDINATION DRAWINGS FOR REVIEW (BETWEEN FURNITURE VENDOR, LAB EQUIPMENT VENDORS & CONTRACTOR) PRIOR TO ROUGH-INS).



KEYPLAN

1" = 100'-0"

Revisions:	Date:

CONSULTANT
 Consultant:
CMTA CONSULTING ENGINEERS, INC.
 10411 MEETING STREET,
 PROSPECT, KY 40059
 (502)326-3085

ARCHITECT/ENGINEER OF RECORD

A/E:
GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388

STAMP

Office of Construction and Facilities Management
 VA U.S. Department of Veterans Affairs

Drawing Title
SECOND FLOOR PLAN - POWER

Approved:


Phase
BID DOCUMENTS

Project Title	Project Number
VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY	589-701
Location WICHITA, KANSAS	Building Number 1 & 1C
Issue Date 05/22/2020	Drawing Number ES301
Checked PDY	Drawn RAH

A B C D E F



1 THIRD FLOOR PLAN - POWER
SCALE: 1/8" = 1'-0"



2 ENLARGED 3RD FLOOR PLAN - ELEC C309
SCALE: 1/4" = 1'-0"





3 ENLARGED 3RD FLOOR PLAN - ELEC C362
SCALE: 1/4" = 1'-0"

SECOND & THIRD FLOOR ALTERNATE OFFICE CUBICLE AREA
REFER TO THE ARCHITECTURAL PLANS FOR A PROPOSED "OPEN OFFICE" AREA LAYOUT ON THE THIRD FLOOR. PROVIDE APPROXIMATELY (20) TYPE "A2" 2X4 LIGHTS, (6) CEILING TYPE VACANCY SENSOR UNITS, (4) LOW VOLTAGE LIGHT SWITCHES, (18) QUADRAPLEX RECEPTACLES, (4) FLOOR FED FURNITURE POWER FEEDS, (4) FLOOR FED FURNITURE DATA FEEDS, (8) "4D" DATA OUTLETS AND (2) FIRE ALARM AUDIO/VISUAL UNITS.

- TAGGED NOTES**
- L1 PROVIDE 120V/1Ø POWER FROM RECEPTACLE CIRCUIT SERVING COUNTER TOP RECEPTACLES BELOW.
 - P1 PROPOSED LOCATION FOR TRANSFORMER DISCONNECT SWITCH AS INDICATED ON POWER RISER. REFER TO POWER RISER FOR SIZING AND EXACT REQUIREMENTS. LOCATE BESIDE TRANSFORMER IN ORDER TO MAINTAIN ALL REQUIRED CLEARANCES.
 - P3 ROUTE ONE (1) #10 GROUND CONDUCTOR IN 1/2" CONDUIT CONTINUOUSLY AROUND ROOM (FULL CIRCLE) CONNECTING TO ALL PANELBOARD GROUND BARS IN ROOM AS REQUIRED BY N.E.C. #517.14. CONTRACTOR SHALL ALSO SUBMIT DETAILED DIMENSIONED SHOP DRAWINGS OF ELECTRIC ROOMS INDICATING PANELBOARD, TRANSFORMER, DISCONNECT SWITCHES, ETC. LOCATIONS AND REQUIRED CLEARANCES.
 - P7 COORDINATE BEST LOCATION FOR RECEPTACLE TO ENSURE ACCESSIBILITY WITH INSTALLATION OF MECHANICAL EQUIPMENT IN THIS ROOM.
 - P17 PROVIDE 4" CONCRETE HOUSEKEEPING PAD FOR EQUIPMENT INDICATED. CONFIRM ALL REQUIRED CLEARANCES FOR EQUIPMENT ARE MAINTAINED PRIOR TO POURING OF CONCRETE.
 - P18 CONCEAL RECEPTACLE BEHIND ELECTRIC WATER COOLER (EWC). COORDINATE EXACT ROUGH-IN LOCATION(S) WITH EQUIPMENT SHOP DRAWINGS PRIOR TO CONSTRUCTION. PROVIDE WITH REMOTE, READILY ACCESSIBLE GFCI DEVICE NEXT TO EWC.
 - P21 PROVIDE ONE (1) 1-1/2" CONDUIT FOR DATA AND HDMI CONNECTIONS TO TV MOUNTED ON WALL IN THIS AREA. CUT, TRENCH, AND PATCH FLOOR AS REQUIRED. EXTEND CONDUIT TO NEAREST AVAILABLE CABLE PATH.


- GENERAL NOTES (POWER):**
- A. THIN SOLID LINES INDICATE EXISTING ITEMS TO REMAIN (U.O.N.) AND THICK SOLID LINES INDICATE NEW WORK.
 - B. ALL NEW WIRING SHALL BE #12 WITH A #12 INSULATED GROUND WIRE (U.O.N.). CONDUIT SHALL BE 3/4" MINIMUM.
 - C. REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
 - D. CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.2(1) & 210.4 (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
 - E. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE CLEAR ADHESIVE LABELS WITH BLACK LETTERING. IN HEALTHCARE FACILITIES, ENGRAVE EMERGENCY DEVICE COVERPLATES IN PATIENT CARE AREAS. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
 - F. RECEPTACLES THAT ARE CONTROLLED BY AN AUTOMATIC MEANS SUCH AS OCCUPANCY SENSOR OR ENERGY MANAGEMENT SYSTEM SHALL BE MARKED IN ACCORDANCE WITH NEC 406.3(E).
 - G. LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.
 - H. NO CONDUIT SHALL BE INSTALLED UNDERGROUND, EXCEPT FOR DISTRIBUTION EQUIPMENT FEEDERS, UNLESS SPECIFIED FOR THE APPLICATION (FLOOR BOXES, ISLANDS, ETC.) OR SPECIFICALLY INDICATED AS SUCH IN CONSTRUCTION DOCUMENTS. NO CONDUIT SHALL BE INSTALLED WITHIN CONCRETE SLABS.
 - I. ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES LABEL INTERIOR OF BOX WHERE "IN WALL" SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT / CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
 - J. ALL CEILING MOUNTED DEVICES, FIXTURES, ETC. SHALL BE INSTALLED COMPLETELY FLUSH WITH FINISHED CEILING. CAREFULLY COORDINATE WITH DRYWALL CONTRACTOR TO ENSURE A FLUSH INSTALLATION. DRYWALL CONTRACTOR SHALL TAPE, MUD, AND SAND AS NEEDED. NO GAP BETWEEN DEVICE/FIXTURE AND CEILING WILL BE ACCEPTABLE. IF DEEMED THE ONLY SOLUTION BY THE ARCHITECT OR ENGINEER, THIS CONTRACTOR SHALL PROVIDE AN APPROVED SEALANT TO SEAL ANY SUCH GAPS THAT EXIST. A FINAL WALK-THROUGH SHALL BE SCHEDULED WITH THE OWNER TO APPROVE THE FINISHED CEILING CONDITION.
 - K. NO CONDUIT, SUPPORTS, ETC. SHALL BE RUN THROUGH ACCESS CLEARANCES OF EQUIPMENT BY OTHER TRADES (I.E. VAV BOXES). COORDINATE WITH ALL TRADES PRIOR TO CONSTRUCTION.
 - L. WHERE ANY RECEPTACLE IS LOCATED WITHIN 6'-0" OF SINK, CONTRACTOR SHALL PROVIDE "GFCI" TYPE OUTLET OR CONNECT CIRCUIT TO A 20A/1P GFCI TYPE CIRCUIT BREAKER. REFER TO ARCHITECTURAL PLANS FOR SINK LOCATIONS.
 - M. PROVIDE COORDINATION DRAWINGS FOR REVIEW (BETWEEN FURNITURE VENDOR, LAB EQUIPMENT VENDORS & CONTRACTOR) PRIOR TO ROUGH-IN(S).



Revisions:	Date:

CONSULTANT
 Consultant:
CMTA CONSULTING ENGINEERS, INC.
 10411 MEETING STREET,
 PROSPECT, KY 40059
 (502)326-3085

ARCHITECT/ENGINEER OF RECORD
 A/E:
GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388



Office of
 Construction
 and Facilities
 Management


U.S. Department
 of Veterans Affairs

Drawing Title	THIRD FLOOR PLAN - POWER
Approved:	


Phase	BID DOCUMENTS
-------	---------------

Project Title	VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY
Location	WICHITA, KANSAS
Issue Date	05/22/2020
Checked	PDY
Drawn	RAH

Project Number	589-701
Building Number	1 & 1C
Drawing Number	ES302



2 BASEMENT FLOOR PLAN - POWER
SCALE: 1/8" = 1'-0"



1 ROOF PLAN - ELECTRICAL
SCALE: 1/8" = 1'-0"

GENERAL NOTES (POWER):

- A. THIN SOLID LINES INDICATE EXISTING ITEMS TO REMAIN (U.O.N.) AND THICK SOLID LINES INDICATE NEW WORK.
- B. ALL NEW WIRING SHALL BE #12 WITH A #12 INSULATED GROUND WIRE (I.O.N.). CONDUIT SHALL BE 3/4" MINIMUM.
- C. REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
- D. CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3) AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.2(10.4) (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
- E. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE CLEAR ADHESIVE LABELS WITH BLACK LETTERING. IN HEALTHCARE FACILITIES, ENGRAVE EMERGENCY DEVICE COVERPLATES IN PATIENT CARE AREAS. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
- F. RECEPTACLES THAT ARE CONTROLLED BY AN AUTOMATIC MEANS SUCH AS OCCUPANCY SENSOR OR ENERGY MANAGEMENT SYSTEM SHALL BE MARKED IN ACCORDANCE WITH NEC 406.3(E).
- G. LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.
- H. NO CONDUIT SHALL BE INSTALLED UNDERGROUND, EXCEPT FOR DISTRIBUTION EQUIPMENT FEEDERS, UNLESS REQUIRED FOR THE APPLICATION (FLOOR BOXES, ISLANDS, ETC.) OR SPECIFICALLY INDICATED AS SUCH IN CONSTRUCTION DOCUMENTS. NO CONDUIT SHALL BE INSTALLED WITHIN CONCRETE SLABS.
- I. ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES LABEL INTERIOR OF BOX WHERE IN WALL/SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT/ CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
- J. ALL CEILING MOUNTED DEVICES, FIXTURES, ETC. SHALL BE INSTALLED COMPLETELY FLUSH WITH FINISHED CEILING. CAREFULLY COORDINATE WITH DRYWALL CONTRACTOR TO ENSURE A FLUSH INSTALLATION. DRYWALL CONTRACTOR SHALL TAPE, MUD, AND SAND AS NEEDED. NO GAP BETWEEN DEVICE/FIXTURE AND CEILING WILL BE ACCEPTABLE. IF DEEMED THE ONLY SOLUTION BY THE ARCHITECT OR ENGINEER, THIS CONTRACTOR SHALL PROVIDE AN APPROVED SEALANT TO SEAL ANY SUCH GAPS THAT EXIST. A FINAL WALK-THROUGH SHALL BE SCHEDULED WITH THE OWNER TO APPROVE THE FINISHED CEILING CONDITION.
- K. NO CONDUIT, SUPPORTS, ETC. SHALL BE RUN THROUGH ACCESS CLEARANCES OF EQUIPMENT BY OTHER TRADES (I.E. VAV BOXES). COORDINATE WITH ALL TRADES PRIOR TO CONSTRUCTION.
- L. WHERE ANY RECEPTACLE IS LOCATED WITHIN 6'-0" OF SINK, CONTRACTOR SHALL PROVIDE "GFCI" TYPE OUTLET OR CONNECT CIRCUIT TO A 20A/1P GFCI TYPE CIRCUIT BREAKER. REFER TO ARCHITECTURAL PLANS FOR SINK LOCATIONS.
- M. PROVIDE COORDINATION DRAWINGS FOR REVIEW (BETWEEN FURNITURE VENDOR, LAB EQUIPMENT VENDORS & CONTRACTOR) PRIOR TO ROUGH-INS.

TAGGED NOTES

- P5 EXISTING ROOF TOP EQUIPMENT RELOCATED FROM FIRST FLOOR ROOF. EXTEND EXISTING POWER UP TO NEW ROOF TOP LOCATION. RECONNECT EXISTING POWER TO NEW DISCONNECT SWITCH AS REQUIRED. FIELD VERIFY EXACT CONDITIONS AND RE-ROUTING REQUIREMENTS PRIOR TO CONSTRUCTION.
- P12 PROVIDE 30A/60V/3P FUSIBLE HEAVY DUTY DISCONNECT SWITCH IN NEMA-3R ENCLOSURE FUSED AT EQUIPMENT NAMEPLATE RATING. COORDINATE DISCONNECT LOCATION WITH ALL TRADES TO ENSURE ALL REQUIRED CLEARANCES ARE MAINTAINED. PROVIDE UNISTRUT FOR MOUNTING OF EQUIPMENT AS REQUIRED. PROVIDE WIRING AND CONDUIT AS REQUIRED FOR A COMPLETE SYSTEM.
- P13 PROVIDE UNISTRUT FOR MOUNTING OF EQUIPMENT AS REQUIRED.
- P14 PROVIDE 30A/250V/3P FUSIBLE HEAVY DUTY DISCONNECT SWITCH IN NEMA-3R ENCLOSURE FUSED AT EQUIPMENT NAMEPLATE RATING. COORDINATE DISCONNECT LOCATION WITH ALL TRADES TO ENSURE ALL REQUIRED CLEARANCES ARE MAINTAINED. PROVIDE UNISTRUT FOR MOUNTING OF EQUIPMENT AS REQUIRED. PROVIDE WIRING AND CONDUIT AS REQUIRED FOR A COMPLETE SYSTEM.
- P23 ROUTE THROUGH MANUFACTURER'S INTEGRAL DISCONNECT SWITCH. REFER TO MECHANICAL SCHEDULES FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
- P24 ROUTE POWER AND CONTROLS THROUGH INDOOR UNIT AS REQUIRED. REFER TO MECHANICAL SCHEDULES FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
- P26 EXISTING EQUIPMENT INDICATED TO REMAIN.
- P27 ROUTE NUMBER OF #10 CONDUCTORS AND ONE (1) #10 GROUND AS INDICATED IN 3/4" CONDUIT TO NEAREST AVAILABLE NEW / SPARE 250A/3P BREAKER(S) IN EXISTING PANEL INDICATED. VERIFY EXACT PANEL LOCATION(S) AND BRANCH CIRCUITING ROUTES PRIOR TO CONSTRUCTION. WHERE EXISTING PANEL IS FLUSH-MOUNTED IN AN EXISTING WALL TO REMAIN, CONTRACTOR SHALL CUT, PATCH, AND REPAIR WALL AS REQUIRED FOR CONCEALED CONDUIT ENTRY.

BID DEDUCTIVE ALTERNATE #2


EXISTING AIR HANDLING UNIT AHU-2 AND RETURN FAN RF-2 SHALL REMAIN. EXISTING DUCTWORK, PIPING, CONTROLS, ELECTRICAL CONNECTIONS, ETC. SERVING AHU-2 AND RF-2 SHALL REMAIN AS IS. ALL WORK ASSOCIATED WITH TEMPORARY AIR HANDLING UNIT SHALL BE REMOVED FROM SCOPE OF WORK.

GENERAL NOTES (ROOF):

- A. REFER TO POWER, SYSTEMS, AND LIGHTING PLANS FOR GENERAL NOTES APPLICABLE TO INTERIOR SPACES SHOWN ON THIS PLAN.
- B. CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.2(10.4) (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
- C. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE ENGRAVED LAMACOD LABELS FOR ALL EXTERIOR DEVICES. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
- D. PROVIDE UNISTRUT AS REQUIRED FOR MOUNTING OF ALL DEVICES ON ROOF. COORDINATE WITH ROOFING CONTRACTOR PRIOR TO CONSTRUCTION FOR ALL PENETRATIONS. SEAL PENETRATIONS AS REQUIRED PER ROOFING CONTRACTOR AND ROOFING MANUFACTURER'S RECOMMENDATIONS AS REQUIRED TO MAINTAIN ROOF WARRANTY. PROVIDE CURBS AND/OR FLASHED BOOTS AT ALL DEVICES AND PENETRATIONS.
- E. CONDUITS SHALL PENETRATE ROOF FROM BELOW AS CLOSE TO FINAL ROOF EQUIPMENT TERMINATION POINT AS POSSIBLE. SUPPORT ALL ROOF MOUNTED CONDUITS AT INTERVALS NOT EXCEEDING 10 FEET WITH STRUT-BASED SUPPORT SYSTEM. SUPPORT SYSTEM TO BE CADDY PYRAMID ST SERIES OR APPROVED EQUAL.
- F. ALL CONDUIT EXPOSED TO DIRECT SUNLIGHT SHALL BE AT LEAST 12" ABOVE THE ROOF-TOP. NO CONDUIT SHALL BE EXPOSED TO DIRECT SUNLIGHT BELOW THIS HEIGHT.
- G. WHERE RACEWAY OR CONDUCTORS ARE INSTALLED EXPOSED ON ROOF, DERATE AMPACITY OF CONDUCTORS IN ACCORDANCE WITH NEC.
- H. LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.
- I. PROVIDE MAINTENANCE RECEPTACLE WITHIN 26 FT OF EACH MECHANICAL UNIT AS REQUIRED BY NEC. COORDINATE INSTALLATION LOCATIONS WITH FINAL EQUIPMENT LAYOUT PROVIDED BY MECHANICAL CONTRACTOR.
- J. CONDUIT FOR ROOF MOUNTED EQUIPMENT SHALL BE ROUTED IN CEILING SPACE BELOW ROOF DECK UNO.

GENERAL NOTES (LIGHTNING PROTECTION):

- A. PROVIDE LIGHTNING PROTECTION SYSTEM EXTENSION FOR BUILDING ADDITION TO THE EXISTING FACILITY. SYSTEM SHALL COMPLY WITH U.L. #96A "MASTER LABELED LIGHTNING PROTECTION SYSTEMS". REFER TO THE ELECTRICAL SPECIFICATIONS.
- B. PENETRATIONS THROUGH SHEET METAL INCLUDING BUT NOT LIMITED TO COPINGS AND COUNTER FLASHINGS, SHALL NOT BE ALLOWED. CONNECTIONS TO PARAPETS SHALL BE BY CLAMPS MADE TO FASTEN TO THE DRIP EDGE OF COPINGS WITHOUT PENETRATION TO AND OF THE COPINGS. REFER TO ARCHITECTURAL ROOF PLANS FOR DETAILS OF PENETRATIONS THROUGH HORIZONTAL ROOF AREAS. PENETRATIONS THROUGH HORIZONTAL ROOF AREAS SHALL BE NO CLOSER THAN 16" TO ANY VERTICAL BUILDING SURFACE.
- C. ALL ROOF PENETRATIONS AND ASSOCIATED LABOR COSTS SHALL BE AT THE EXPENSE OF THIS CONTRACTOR, BUT SHALL BE INSTALLED BY THE ROOFING CONTRACTOR IN ORDER TO MAINTAIN ANY APPLICABLE ROOF WARRANTIES. ANY DEVIATIONS NECESSARY BY THIS CONTRACTOR SHALL FIRST BE SUBMITTED TO THE ARCHITECT'S OFFICE FOR REVIEW. ANY COSTS ASSOCIATED WITH CHANGES TO THIS SYSTEM THAT ARE A RESULT OF PROPOSED DETAILS NOT BEING ACCEPTABLE TO THE OWNER, ARCHITECT, OR ENGINEER SHALL BE AT THE EXPENSE OF THIS CONTRACTOR. ALL REQUIRED CONNECTION DEVICES SHALL BE REVIEWED BY THE ARCHITECT AND ENGINEER. PENETRATION DEVICES THROUGH STANDING SEAM METAL ROOF AREAS SHALL BE PROVIDED BY THE SHEET METAL ROOFING CONTRACTOR.



KEYPLAN
1" = 100'-0"

Revisions:	Date:

CONSULTANT
 Consultant:
CMTA CONSULTING ENGINEERS, INC.
 10411 MEETING STREET,
 PROSPECT, KY 40059
 (502)326-3085

ARCHITECT/ENGINEER OF RECORD STAMP
 A/E:
GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388

Office of Construction and Facilities Management
VA U.S. Department of Veterans Affairs

Drawing Title
BASEMENT AND ROOF PLAN - ELECTRICAL

Approved:

Phase
BID DOCUMENTS

Project Title VAS WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY	Project Number 589-701
Location WICHITA, KANSAS	Building Number 1 & 1C
Issue Date 05/22/2020	Checked PDY
Drawn RAH	Drawing Number ES303

SECOND & THIRD FLOOR ALTERNATE OFFICE CUBICLE AREA



REFER TO THE ARCHITECTURAL PLANS FOR A PROPOSED "OPEN OFFICE" AREA LAYOUT ON THE THIRD FLOOR. PROVIDE APPROXIMATELY (20) TYPE "A2" 2X4 LIGHTS, (6) CEILING TYPE VACANCY SENSOR UNITS, (4) LOW VOLTAGE LIGHT SWITCHES, (18) QUADRAPLEX RECEPTACLES, (4) FLOOR FED FURNITURE POWER FEEDS, (4) FLOOR FED FURNITURE DATA FEEDS, (8) '4D' DATA OUTLETS AND (2) FIRE ALARM AUDIO/VISUAL UNITS.

GENERAL NOTES (SYSTEMS):

- A. REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
- B. CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.1(2) 4 CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR SHALL NOT BE PERMITTED.
- C. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE CLEAR ADHESIVE LABELS WITH BLACK LETTERING. IN HEALTHCARE FACILITIES, ENGRAVE EMERGENCY DEVICE COVERPLATES IN PATIENT CARE AREAS. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
- D. REFER TO "SYSTEM INSTALLATION MATRIX" (ON SYSTEMS LEGEND SHEET) AND SPECIFICATIONS FOR CONTRACTOR REQUIREMENTS OF EACH SYSTEM.
- E. THE CONTRACTOR SHALL ROUTE ALL "SYSTEM CONDUIT STUB-UPS" TO THE NEAREST CORRIDOR CABLING PATH (SEE "STUB-UP" DETAILS). REFER TO CABLING PATH INSTALLATION DETAIL FOR ADDITIONAL REQUIREMENTS.
- F. CONTRACTOR SHALL PAINT ALL SYSTEMS CONDUIT STUB-UPS LIGHT BLUE FOR SYSTEMS CABLING INTO THE CORRIDOR CABLING PATH. PROVIDE PULL STRINGS IN ALL NEW CONDUIT RUNS FOR SYSTEM CABLING INSTALLATION.

TAGGED NOTES


- S2 ROUTE ONE (1) 1-1/4" CONDUIT FROM POKE-THRU TO STUB UP INSIDE WALL FOR AV, HDMI, DATA, ETC. CONNECTIONS BETWEEN POKE THRU AND TV. COORDINATE EXACT POKE THRU AND TV LOCATION PRIOR TO ROUGH-IN.
- S14 PROVIDE FOUR (1) 2" CONDUIT SLEEVE(S) THROUGH WALL(S) INDICATED. INSTALL SLEEVE(S) ABOVE SUSPENDED CEILING (WHERE APPLICABLE). PROVIDE UL LISTED FIRE-RATED ASSEMBLY AT PENETRATION AS REQUIRED. REFER TO SLEEVE PENETRATION DETAIL FOR ADDITIONAL REQUIREMENTS (TYPICAL ALL PENETRATIONS).
- S17 PROVIDE CONNECTION TO FIRE ALARM SYSTEM FOR AUTOMATIC RELEASE OF ALL MECHANICALLY HELD DOORS UPON FIRE ALARM SYSTEM ACTIVATION. REFER TO FIRE ALARM RISER DIAGRAM FOR ADDITIONAL REQUIREMENTS AND INFORMATION.



KEYPLAN
1" = 100'-0"


1 THIRD FLOOR PLAN - SYSTEMS
SCALE: 1/8" = 1'-0"
0 2' 4' 8' 16' 24' 32'

CONSULTANT Consultant: CMTA CONSULTING ENGINEERS, INC. 10411 MEETING STREET, PROSPECT, KY 40059 (502)326-3085 		ARCHITECT/ENGINEER OF RECORD A/E: GUIDON DESIGN, INC 1221 N PENNSYLVANIA STREET INDIANAPOLIS, IN 46202 (317) 800-6388 		STAMP 		Office of Construction and Facilities Management U.S. Department of Veterans Affairs		Drawing Title THIRD FLOOR PLAN - SYSTEMS Approved:		Phase BID DOCUMENTS		Project Title VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY Project Number 589-701 Building Number 1 & 1C	
Revisions:		Date:		Location WICHITA, KANSAS		Issue Date 05/22/2020		Checked PDY		Drawn RAH		Drawing Number ES402	




4 ENLARGED 2ND FLOOR PLAN - DATA C208

SCALE: 1/4" = 1'-0"




2 ENLARGED 2ND FLOOR PLAN - I.T. 243

SCALE: 1/4" = 1'-0"



5 ENLARGED 3RD FLOOR PLAN - DATA C310

SCALE: 1/4" = 1'-0"



6 ENLARGED 3RD FLOOR PLAN - BIOMED 345


SCALE: 1/4" = 1'-0"

ROUTE ALL NEW DATA/VOICE CABLING (UON) FROM NEW DEVICES LOCATED ON THIS FLOOR LEVEL TO THIS NEW DATA CLOSET AS INDICATED ON DRAWING ES501

ROUTE ALL NEW DATA/VOICE CABLING (UON) FROM NEW DEVICES LOCATED ON THIS FLOOR LEVEL TO THIS NEW DATA CLOSET AS INDICATED ON DRAWING ES801

1 SECOND FLOOR PLAN - CABLING PATH

1/16" = 1'-0"



3 THIRD FLOOR PLAN - CABLING PATH


1/16" = 1'-0"

GENERAL NOTES (INTERCONNECTION):

- A. THE CONTRACTOR SHALL VISIT SITE AND VERIFY THAT PULL BOXES AND CONDUITS MAY BE INSTALLED AS INDICATED. IF THERE IS A CONFLICT, CONTRACTOR SHALL NOTIFY ENGINEER 10 DAYS PRIOR TO BID. NO PRICE CHANGE WILL BE GIVEN FOR ANY ALTERNATE ROUTINGS OF CONDUIT AFTER THE CONTRACT HAS BEEN AWARDED. NOTIFY FACILITY ENGINEER AT LEAST 24 HOURS IN ADVANCE OF ANY VISIT.
- B. ALL NEW WORK SHALL BE HUNG FROM STRUCTURE, NOT FROM THE WORK OF OTHER TRADES (WHETHER EXISTING OR NEW).
- C. COORDINATE ALL WORK WITH ARCHITECTURAL, MECHANICAL, PHASING AND APPROPRIATE FACILITY STAFF. WORK IN CERTAIN AREAS SHALL BE DONE ON WEEKENDS AND/OR AT NIGHT. COORDINATE ALL REQUIREMENTS WITH ARCHITECT/OWNER PRIOR TO BID.
- D. REMOVE AND RE-INSTALL ALL CEILING TILES FROM DESIGNATED ROOM(S) AND USE THESE TO REPLACE DAMAGED CEILING TILES. ALL NEW CEILING TILES SHALL BE INSTALLED IN "DESIGNATED" ROOM(S) AT CLOSE OF PROJECT. COORDINATE "DESIGNATED" ROOM(S) WITH FACILITY ENGINEER. REPLACE TILES WITH NEW IF ACCEPTABLE TO OWNER.

TAGGED NOTES

- P11 ROUTE NUMBER OF #12 CONDUCTORS AND ONE (1) #12 GROUND AS INDICATED IN 3/4" CONDUIT TO NEAREST AVAILABLE NEW 20A/1P BREAKER(S) IN EXISTING PANEL INDICATED. VERIFY EXACT PANEL LOCATION(S) AND BRANCH CIRCUITING ROUTES PRIOR TO CONSTRUCTION. WHERE EXISTING PANEL IS FLUSH MOUNTED IN AN EXISTING WALL TO REMAIN, CONTRACTOR SHALL CUT, PATCH, AND REPAIR WALL AS REQUIRED FOR CONCEALED CONDUIT ENTRY.
- P19 PROVIDE NEMA #14-30R RECEPTACLE FOR DATA RACK 6-KVA UPS UNIT.
- S5 PROVIDE TWO (2) 2" CONDUIT SLEEVE(S) THROUGH WALL(S) INDICATED. INSTALL SLEEVE(S) ABOVE SUSPENDED CEILING (WHERE APPLICABLE) IN-LINE WITH CABLING PATH. PROVIDE UL LISTED FIRE-RATED ASSEMBLY AT PENETRATION AS REQUIRED. REFER TO SLEEVE PENETRATION DETAIL FOR ADDITIONAL REQUIREMENTS (TYPICAL ALL PENETRATIONS).
- S6 PROVIDE FOUR (3) 4" CONDUIT SLEEVE(S) THROUGH WALL(S) INDICATED. INSTALL SLEEVE(S) ABOVE SUSPENDED CEILING (WHERE APPLICABLE) IN-LINE WITH CABLING PATH. PROVIDE UL LISTED FIRE-RATED ASSEMBLY AT PENETRATION AS REQUIRED. REFER TO SLEEVE PENETRATION DETAIL FOR ADDITIONAL REQUIREMENTS (TYPICAL ALL PENETRATIONS).
- S7 PROPOSED J-HOOK CABLING PATH. REFER TO J-HOOK DETAIL FOR ADDITIONAL REQUIREMENTS.
- S8 MOUNT RECEPTACLES TO CABLE TRAY ABOVE.
- S11 PROVIDE 4" CONDUIT FOR NEW PANEL "1C-NH3C" DOWN TO FLOOR BELOW. ROUTE THROUGH EXISTING PARTS OF THE FACILITY AND FIELD VERIFY BEST ROUTING PRIOR TO CONSTRUCTION. REFER TO POWER DISTRIBUTION RISER DIAGRAM FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
- S12 PROVIDE FOUR (1) 4" CONDUIT SLEEVE(S) THROUGH WALL(S) INDICATED. INSTALL SLEEVE(S) ABOVE SUSPENDED CEILING (WHERE APPLICABLE). PROVIDE UL LISTED FIRE-RATED ASSEMBLY AT PENETRATION AS REQUIRED. REFER TO SLEEVE PENETRATION DETAIL FOR ADDITIONAL REQUIREMENTS (TYPICAL ALL PENETRATIONS).
- S13 PROVIDE 1-1/4" CONDUIT FOR NEW PANEL "1C-NH3C" DOWN TO FLOOR BELOW. ROUTE THROUGH EXISTING PARTS OF THE FACILITY AND FIELD VERIFY BEST ROUTING PRIOR TO CONSTRUCTION. REFER TO POWER DISTRIBUTION RISER DIAGRAM FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
- S14 PROVIDE FOUR (1) 2" CONDUIT SLEEVE(S) THROUGH WALL(S) INDICATED. INSTALL SLEEVE(S) ABOVE SUSPENDED CEILING (WHERE APPLICABLE). PROVIDE UL LISTED FIRE-RATED ASSEMBLY AT PENETRATION AS REQUIRED. REFER TO SLEEVE PENETRATION DETAIL FOR ADDITIONAL REQUIREMENTS (TYPICAL ALL PENETRATIONS).



KEYPLAN

1" = 100'-0"

Revisions:	Date:

CONSULTANT
 Consultant:
CMTA CONSULTING ENGINEERS, INC.
 10411 MEETING STREET,
 INDIANAPOLIS, KY 40059
 (502)326-3085

ARCHITECT/ENGINEER OF RECORD
 A/E:
GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388

STAMP
 STATE OF KANSAS
 ROBERT ANTHONY HANS
 21246
 PROFESSIONAL ENGINEER

Office of Construction and Facilities Management
 VA U.S. Department of Veterans Affairs

Drawing Title
 SECOND AND THIRD FLOOR - CABLING PATH PLANS

Approved:

Phase
 BID DOCUMENTS


Project Title
 VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY

Location
 WICHITA, KANSAS


Project Number
 589-701

Building Number
 1 & 1C


Drawing Number
 ES501




1 ENLARGED 3RD FLOOR PLAN - TYPICAL PATIENT ROOM - LIGHTING




2 ENLARGED 3RD FLOOR PLAN - TYPICAL PATIENT ROOM - POWER / SYSTEMS



3 ENLARGED 3RD FLOOR PLAN - TYPICAL ISOLATION PATIENT ROOM - LIGHTING




4 ENLARGED 3RD FLOOR PLAN - TYPICAL ISOLATION PATIENT ROOM - POWER / SYSTEMS




- GENERAL NOTES (ROOF):**
- REFER TO POWER, SYSTEMS, AND LIGHTING PLANS FOR GENERAL NOTES APPLICABLE TO INTERIOR SPACES SHOWN ON THIS PLAN.
 - CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.2(1) (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
 - IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE CLEAR ADHESIVE LABELS WITH BLACK LETTERING IN HEALTHCARE FACILITIES. ENGRAVE EMERGENCY DEVICE COVERPLATES IN PATIENT CARE AREAS. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
 - PROVIDE UN-STRUT AS REQUIRED FOR MOUNTING OF ALL DEVICES ON ROOF. COORDINATE WITH ROOFING CONTRACTOR PRIOR TO CONSTRUCTION FOR ALL PENETRATIONS. SEAL PENETRATIONS AS REQUIRED PER ROOFING CONTRACTOR AND ROOFING MANUFACTURER'S RECOMMENDATIONS AS REQUIRED TO MAINTAIN ROOF WARRANTY. PROVIDE CURBS AND/OR FLASHED BOOTS AT ALL DEVICES AND PENETRATIONS.
 - CONDUITS SHALL PENETRATE ROOF FROM BELOW AS CLOSE TO FINAL ROOF EQUIPMENT TERMINATION POINT AS POSSIBLE. SUPPORT ALL ROOF MOUNTED CONDUITS AT INTERVALS NOT EXCEEDING 10 FEET WITH STRUT-BASED SUPPORT SYSTEM. SUPPORT SYSTEM TO BE CADDY PYRAMID ST SERIES OR APPROVED EQUAL.
 - ALL CONDUIT TO BE USED TO DIRECT SUNLIGHT SHALL BE AT LEAST 12" ABOVE THE ROOF-TOP. NO CONDUIT SHALL BE EXPOSED TO DIRECT SUNLIGHT BELOW THIS HEIGHT.
 - WHERE RACEWAY OR CONDUITS ARE INSTALLED EXPOSED ON ROOF, DERATE AMPACITY OF CONDUITS IN ACCORDANCE WITH NEC.
 - LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.
 - PROVIDE MAINTENANCE RECEPTACLE WITHIN 25 FT OF EACH MECHANICAL UNIT AS REQUIRED BY NEC. COORDINATE INSTALLATION LOCATIONS WITH FINAL EQUIPMENT LAYOUT PROVIDED BY MECHANICAL CONTRACTOR.
 - CEILING MOUNTED EQUIPMENT SHALL BE ROUTED IN CONDUIT SPACE BELOW ROOF DECK UNO.
- GENERAL NOTES (ENLARGED AND TYPICAL):**
- ALL ROOM LAYOUTS ARE TYPICAL AND MAY VARY OR MIRROR OTHER ASSOCIATED ROOMS. CONTRACTOR SHALL REFER TO ARCHITECTURAL ELEVATIONS AND COORDINATE EACH ROOM PRIOR TO ROUGH-IN.
- GENERAL NOTES (LIGHTING):**
- REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
 - CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER N.E.C. #300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN N.E.C #100.2(1) (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
 - ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES (LABEL INTERIOR OF BOX WHERE "IN WALL" SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT / CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
 - LOCATE CHAIN-HUNG INDUSTRIAL FIXTURES IN MECHANICAL ROOMS TO AVOID DUCTWORK AND PIPING. TO MAXIMIZE AVAILABLE LIGHT, SPACE AROUND EQUIPMENT, AIR HANDLERS, ETC. TO PROVIDE ADEQUATE LIGHTING TO ALL AREAS OF ROOM. PROVIDE ADDITIONAL FIXTURES OF SAME TYPE AS NEEDED TO FULFILL THIS REQUIREMENT.
 - LOCATE EXIT SIGNS FOR MAXIMUM VIEWING. CONTRACTOR SHALL IDENTIFY EGRESS PATHS AS INDICATED ON PLANS. COORDINATE LOCATIONS SUCH THAT ARCHITECTURAL FEATURES OR EQUIPMENT FROM OTHER TRADES DO NOT OBSTRUCT VIEWING.
 - WHERE EXIT SIGNS OR EMERGENCY BATTERY PACKS ARE PROVIDED, THEY SHALL BE CONNECTED TO AN UNSWITCHED LINE.
 - LUMINAIRES INDICATED WITH MULTIPLE LAMPS SHALL HAVE SIMILAR LAMPS CONTROLLED TOGETHER, I.E. INBOARD AND OUTBOARD LAMPS OR RIGHT AND LEFT HAND LAMPS.
 - ALL LIGHTING FIXTURE LENSES, PARABOLIC LOUVERS, DOWNLIGHTING ALZAK CONES AND "PARACUBE" LOUVERS SHALL BE HANDLED WITH COTTON GLOVES DURING INSTALLATION AND LAMPING TO AVOID FINGERPRINTS OR DIRT DEPOSITS. IF LOUVER OR CONE IS SHIPPED AND INSTALLED WITH CLEAR PLASTIC BAGS TO PROTECT LAMPS. AT CLOSE OF PROJECT, AND AFTER CONSTRUCTION AIR FILTERS ARE CHANGED, REMOVE BAGS. ANY LOUVER OR CONE SHOWING DIRT OR FINGER PRINTS SHALL BE CLEANED WITH SOLVENT RECOMMENDED BY THE MANUFACTURER, OR REPLACED AS NECESSARY IN ORDER TO TURN OVER TO THE OWNER NEW FIXTURES AT OCCUPANCY.
 - RECESSED LUMINAIRES SHALL BE SECURED SUCH THAT THE FORCE REQUIRED INSERTING LAMPS, TRIMS, LENSES, LOUVERS, OR DOOR FLAMES DOES NOT SHIFT HOUSING. ALL TRIMS SHALL BE COMPLETELY FLUSH WITH FINISHED CEILING AT COMPLETION OF CONSTRUCTION.
 - CONTRACTOR SHALL PROVIDE CLEAR ADHESIVE LABELS TO ALL EXIT SIGNS, EMERGENCY INVERTER BATTERY PACKS, AND NIGHT LIGHTS AS REQUIRED.
- GENERAL NOTES (POWER / SYSTEMS):**
- THIN SOLID LINES INDICATE EXISTING ITEMS TO REMAIN (U.O.N.) AND THICK SOLID LINES INDICATE NEW WORK.
 - ALL NEW WIRING SHALL BE #12 WITH A #12 INSULATED GROUND WIRE (U.O.N.). CONDUIT SHALL BE 3/4" MINIMUM.
 - REFER TO THE ARCHITECT'S REFLECTED CEILING PLANS, ELEVATIONS, AND CASEWORK DETAILS FOR EXACT LOCATIONS OF ALL WALL AND CEILING MOUNTED ELECTRICAL DEVICES.
 - CONTRACTOR SHALL FOLLOW BRANCH CIRCUITING LAY-OUT, AS INDICATED ON THE FLOOR PLANS, WITH A MAXIMUM OF THREE (3) BRANCH CIRCUITS PER HOMERUN. EACH BRANCH CIRCUIT SHALL BE PROVIDED WITH A DEDICATED NEUTRAL CONDUCTOR. DEDICATED NEUTRAL CONDUCTORS SHALL BE CONSIDERED CURRENT CARRYING. IF ADDITIONAL CONDUCTORS ARE RAN IN THE SAME CONDUIT WITH THOSE INDICATED, CONTRACTOR SHALL DERATE ALL CURRENT CARRYING CONDUCTORS PER NEC 310.15(B)(3), AND UPSIZE CONDUIT AS REQUIRED PER NEC 300.17 AND ANNEX C. MULTIWIRE BRANCH CIRCUITS AS DEFINED IN NEC 100.2(1) (CIRCUITS SHARING A COMMON NEUTRAL CONDUCTOR) SHALL NOT BE PERMITTED.
 - IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. PROVIDE CLEAR ADHESIVE LABELS WITH BLACK LETTERING IN HEALTHCARE FACILITIES. ENGRAVE EMERGENCY DEVICE COVERPLATES IN PATIENT CARE AREAS. MARK INSIDES OF ALL DEVICE BOXES WITH PANEL AND CIRCUIT NUMBER.
 - RECEPTACLES THAT ARE CONTROLLED BY AN AUTOMATIC MEANS SUCH AS OCCUPANCY SENSOR OR ENERGY MANAGEMENT SYSTEM SHALL BE MARKED IN ACCORDANCE WITH NEC 406.3(E).
 - LOCATIONS OF ELECTRICAL CONNECTIONS AND LOCAL DISCONNECTS SHALL BE COORDINATED WITH MECHANICAL AND PLUMBING CONTRACTORS TO ENSURE ACCESS AND WORKING CLEARANCE IS MAINTAINED PER NEC. NOTIFY OTHER TRADES OF REQUIRED CLEARANCE AREAS TO AVOID ROUTING OF OTHER SYSTEMS IN THESE AREAS. DO NOT INSTALL ELECTRICAL EQUIPMENT OVER EQUIPMENT NAMEPLATES OR ACCESS PANELS OR THROUGH ACCESS/MAINTENANCE CLEARANCES OF EQUIPMENT BY OTHER TRADES.
 - NO CONDUIT SHALL BE INSTALLED UNDERGROUND, EXCEPT FOR DISTRIBUTION EQUIPMENT FEEDERS, UNLESS REQUIRED FOR THE APPLICATION (FLOOR BOXES, ISLANDS, ETC.) OR SPECIFICALLY INDICATED AS SUCH IN CONSTRUCTION DOCUMENTS. NO CONDUIT SHALL BE INSTALLED WITHIN CONCRETE SLABS.
 - ALL DEVICE COVERPLATES SHALL BE #302 STAINLESS STEEL. IDENTIFY THE PANEL AND CIRCUIT NUMBER FOR ALL RECEPTACLES, SWITCHES, ETC. IN AREA OF CONSTRUCTION. ENGRAVE CLEAR ADHESIVE LABELS WITH BLACK LETTERING IN HEALTHCARE FACILITIES. ENGRAVE EMERGENCY DEVICE COVERPLATES FOR IDENTIFICATION. ALL JUNCTION BOXES (LABEL INTERIOR OF BOX WHERE "IN WALL" SWITCHES AND OUTLET BOXES) SHALL BE LABELED WITH THE VOLTAGE, PHASE, CIRCUIT NUMBER AND PANEL OF ORIGIN. A BLACK MARKER SHALL BE ACCEPTABLE FOR JUNCTION BOX LABELING. ALL CONDUCTORS IN A SINGLE CONDUIT / CONDUIT BODY SHALL ORIGINATE FROM THE SAME PANEL. THE GROUND CONDUCTOR SHALL BE BONDED TO THE BOX AT ANY DEVICE OR JUNCTION BOX WHICH HAS CONNECTIONS IN IT.
 - ALL CEILING MOUNTED DEVICES, FIXTURES, ETC. SHALL BE INSTALLED COMPLETELY FLUSH WITH FINISHED CEILING. CAREFULLY COORDINATE WITH DRYWALL CONTRACTOR TO ENSURE A FLUSH INSTALLATION. DRYWALL CONTRACTOR SHALL TAPE, MUD, AND SAND AS NEEDED. NO GAP BETWEEN DEVICE/FIXTURE AND CEILING WILL BE ACCEPTABLE. IF DEEMED THE ONLY SOLUTION BY THE ARCHITECT OR ENGINEER, THIS CONTRACTOR SHALL PROVIDE AN APPROVED SEALANT TO SEAL ANY SUCH GAPS THAT EXIST. A FINAL WALK-THROUGH SHALL BE SCHEDULED WITH THE OWNER TO APPROVE THE FINISHED CEILING CONDITION.
 - NO CONDUIT, SUPPORTS, ETC. SHALL BE RUN THROUGH ACCESS CLEARANCES OF EQUIPMENT BY OTHER TRADES (I.E. VAV BOXES). COORDINATE WITH ALL TRADES PRIOR TO CONSTRUCTION.
 - WHERE ANY RECEPTACLE IS LOCATED WITHIN 6'-0" OF SINK, CONTRACTOR SHALL PROVIDE "GFCI" TYPE OUTLET OR CONNECT CIRCUIT TO A 30A/1P GFCI TYPE CIRCUIT BREAKER. REFER TO ARCHITECTURAL PLANS FOR SINK LOCATIONS.
 - PROVIDE COORDINATION DRAWINGS FOR REVIEW (BETWEEN FURNITURE VENDOR, LAB EQUIPMENT VENDORS & CONTRACTOR) PRIOR TO ROUGH-IN(S).

TAGGED NOTES


D9	EXISTING EQUIPMENT INDICATED TO REMAIN AS IS.
L1	PROVIDE 120V/1Ø POWER FROM RECEPTACLE CIRCUIT SERVING COUNTER TOP RECEPTACLES BELOW.
L2	REFER TO FLOOR PLANS FOR LIGHTING CIRCUIT CONTINUATION.
L5	REFER TO ARCHITECT'S DRAWINGS, DETAILS, ELEVATIONS, ETC. FOR ADDITIONAL REQUIREMENTS, EQUIPMENT LOCATIONS, ETC. FOR ALL TYPICAL PATIENT ROOMS.
P2	PROVIDE 120V/1Ø CONNECTION FOR PATIENT LIFT. VERIFY EXACT REQUIREMENTS WITH MANUFACTURER'S RECOMMENDATIONS PRIOR TO ROUGH-IN.
P4	JUNCTION BOX MOUNTED ABOVE ACCESSIBLE CEILING DIRECTLY ABOVE PATIENT BED HEAD WALL UNIT. CONNECT NORMAL AND EMERGENCY CRITICAL BRANCH POWER CIRCUITS TO HEAD WALL UNIT AS REQUIRED. REFER TO ARCHITECT'S PATIENT HEADWALL UNIT DETAIL FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
P10	REFER TO FLOOR PLANS FOR POWER CIRCUITING CONTINUATION.
P16	REFER TO ARCHITECT'S DRAWINGS, DETAILS, ELEVATIONS, ETC. FOR ADDITIONAL REQUIREMENTS, EQUIPMENT LOCATIONS, ETC. FOR ALL TYPICAL PATIENT ROOMS.
P23	ROUTE THROUGH MANUFACTURER'S INTEGRAL DISCONNECT SWITCH. REFER TO MECHANICAL SCHEDULES FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
S1	NURSE CALL PATIENT BED INTERFACE AND CODE BLUE STATION TO BE INSTALLED IN PRE-MANUFACTURED HEAD WALL. COORDINATE EXACT REQUIREMENTS WITH FINAL HEADWALL SELECTIONS AND MANUFACTURER'S SPECIFICATIONS. REFER TO ARCHITECT'S PATIENT HEADWALL UNIT DETAIL FOR ADDITIONAL REQUIREMENTS AND INFORMATION.
S16	PROVIDE JUNCTION BOX MOUNTED ABOVE ACCESSIBLE CEILING DIRECTLY ABOVE PATIENT BED HEAD WALL UNIT FOR DATA CONNECTION AS REQUIRED. REFER TO ARCHITECT'S PATIENT HEADWALL UNIT DETAIL FOR ADDITIONAL REQUIREMENTS AND INFORMATION.



6 ENLARGED 3RD FLOOR PLAN - TYPICAL BARIATRIC PATIENT ROOM - LIGHTING



5 ENLARGED 3RD FLOOR PLAN - TYPICAL BARIATRIC PATIENT ROOM - POWER / SYSTEMS



7 ATTIC PLAN - ELECTRICAL



5/21/2020 5:47:58 PM C:\Users\mjspring\Documents\WV1919 ELEC R18_2_msp\p18E22R.vrt

Revisions:	Date:

CONSULTANT

Consultant:
CMTA CONSULTING ENGINEERS, INC.
 10411 MEETING STREET,
 PROSPECT, KY 40059
 (502)326-3085

ARCHITECT/ENGINEER OF RECORD

A/E:
GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388

STAMP

Office of Construction and Facilities Management

VA U.S. Department of Veterans Affairs

Drawing Title
ENLARGED PLANS

Approved:

Phase
BID DOCUMENTS

Project Title VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY	Project Number 589-701
Location WICHITA, KANSAS	Building Number 1 & 1C
Issue Date 05/22/2020	Drawing Number ESS02
Checked PDY	Drawn RAH

POWER RISER GENERAL NOTES :

- ALL CONDUCTORS SHALL BE COPPER (SEE SPECIFICATIONS FOR TYPES).
- REFER TO DETAIL FOR TYPICAL PANEL LABELLING REQUIREMENTS.
- ALL "I-LINE" PANELS SHALL BE AS SCHEDULED ON THIS RISER (EXCEPT WHERE INDICATED, THE CONTRACTOR SHALL REFER TO THE PANELBOARD SCHEDULES FOR COMPLETE BREAKER SCHEDULE).
- AS PART OF THIS CONTRACT, PROVIDE A COMPREHENSIVE ARC FLASH HAZARD ANALYSIS FOR POWER DISTRIBUTION DEVICES ON THIS PROJECT. PROVIDE ALL LABELS, WARNING SIGNAGE, ETC. PER NFPA-70E AND OSHA REQUIREMENTS.
- CONTRACTOR SHALL INSTALL SEPARATE CONDUITS, PULL BOXES, ETC. FOR EACH EMERGENCY POWER BRANCH & NORMAL POWER PER N.E.C. #517-30 (C)(1) FOR COMPLETE SEPARATION OF POWER SERVICES.

● AS PART OF THIS CONTRACT, PROVIDE A COORDINATION/FAULT CURRENT STUDY FOR BREAKERS ON THIS PROJECT. STUDY SHALL INCLUDE ALL MAINS AND FEEDERS SHOWN ON THESE DRAWINGS AND SHALL EXTEND TO THE MAIN LUGS OR BREAKER OF THE FURTHEST DEVICE DOWNSTREAM. ALL NEW BREAKERS ON THE EMERGENCY POWER SYSTEM SHALL BE SELECTIVELY COORDINATED TO 0.1 SECONDS PER NEC (NFPA-70) #700.25. EQUIPMENT PRESENTLY SHOWN IS THE BASIS OF DESIGN - OTHER MANUFACTURERS LISTED AS EQUALS MAY NEED TO MODIFY LAYOUTS AND EQUIPMENT IN ORDER TO MEET THIS REQUIREMENT. ALL MANUFACTURERS MUST UTILIZE ELECTRONIC TRIP BREAKERS WITH ADJUSTABLE TRIP SETTINGS WHERE REQUIRED TO MEET SELECTIVE COORDINATION REQUIREMENTS. WHERE MODIFICATION TO EQUIPMENT INDICATED ON THESE DRAWINGS IS REQUIRED IN ORDER TO ACHIEVE COORDINATION, THESE CHANGES SHALL BE CLEARLY NOTED IN THE STUDY. WHERE ACTUAL BREAKER AMPCITIES ARE INCREASED TO ACHIEVE COORDINATION, THE CONTRACTOR IS RESPONSIBLE FOR INCLUDING ALL COST ASSOCIATED WITH THESE CHANGES IN THEIR BID (INCLUDING INCREASES IN FEEDER SIZES). SUBMIT STUDY AS SHOP DRAWING TO ENGINEER PRIOR TO ORDERING ANY POWER DISTRIBUTION EQUIPMENT. ANY EQUIPMENT SUBMITTED PRIOR TO SUBMISSION OF THIS STUDY WILL NOT BE REVIEWED.

PANELBOARD SCHEDULE SYMBOLS :

GFI PROVIDE G.F.C.I. TYPE CIRCUIT BREAKER

PANELBOARD SCHEDULE NOTES :

A. ALL NEW PANELBOARDS SHALL BE ORDERED WITH "DOOR-IN-DOOR" OPTION.
 B. PROVIDE LOCK-OUT TYPE CIRCUIT BREAKERS FOR ALL HARD-WIRED EQUIPMENT.
 C. REFER TO SPECIFICATIONS FOR EQUAL PANELBOARD MANUFACTURERS.
 D. PROVIDE NEW TYPE WRITTEN PANEL DIRECTORIES AT ALL PANELBOARDS. PANEL DIRECTORIES SHALL NOT BE COPIED FROM THESE DRAWINGS. DIRECTORIES SHALL BE DETAILED AND COORDINATED WITH FINAL ROOM NUMBERS, IT RACK NAMES, WORKSTATION DESIGNATIONS, ETC.
 E. PROVIDE NEW PANELBOARD KEY LOCK KITS AT ALL NEW PANEL TRIMS TO MATCH EXISTING AT FACILITY.

SPARE CONDUIT NOTE:

PROVIDE (4) SPARE 1" CONDUITS TO ACCESSIBLE CEILING FROM ALL NEW RECESSED PANELBOARDS.


FEEDER SCHEDULE :

- A. PROVIDE (3) #3, (1) #8 GROUND IN 1-1/4" CONDUIT.
- B. PROVIDE (3) #4/0, (1) #6 GROUND IN 2-1/2" CONDUIT.
- C. PROVIDE (3) #500 Kcmil, (1) #3 GROUND IN 4" CONDUIT.
- D. PROVIDE (3) #2/0, (1) #6 GROUND IN 2" CONDUIT.
- E. PROVIDE (3) #1, (1) #6 GROUND IN 1-1/2" CONDUIT.
- F. PROVIDE (3) #8, (1) #6 GROUND IN 2" CONDUIT.

POWER RISER TAGGED NOTES :

- ① PROVIDE AN INDIVIDUALLY MOUNTED MOLDED CASE BREAKER MOUNTED IN A FLUSH, NEMA-1 ENCLOSURE (SIZE AS NOTED) FOR NEC REQUIRED LOCAL DISCONNECTING MEANS.
- ② INTERCEPT EXISTING POWER FEEDER AT NEW JUNCTION BOX AS REQUIRED.

POWER RISER LINE LEGEND



ELEC RISER - PANEL SUMMARY


PANEL NAME	LOCATION	FED FROM	VOLTAGE	NUMBER OF POLES	PANEL RATING	MAINS	AIC	MOUNTING
1-ELCB3E	ELEC CLOSET 362	1-2-E-3M	208 V	3	225 A	225A/3P MCB	22	SURFACE
1-ELL3E	ELEC CLOSET 362	EMD1	208 V	3	100 A	MLO	22	SURFACE
1-ELL3E	ELEC CLOSET 362	EE8602	208 V	3	100 A	MLO	22	SURFACE
1-NL3E	ELEC CLOSET 362	EE7806A	208 V	3	225 A	225A/3P MCB	22	SURFACE
1C-NL3C	ELEC CLOSET C309	MEP	480 V	3	400 A	MLO	22	SURFACE
1C-NL2C	ELEC C207	1-1C-NL2C	208 V	3	100 A	225A/3P MCB	22	SURFACE
1C-NL3C	ELEC CLOSET C309	1-1C-NL3C	208 V	3	225 A	225A/3P MCB	22	SURFACE

REFER TO "POWER DISTRIBUTION RISER DIAGRAM" ON SHEET ES601 FOR ADDITIONAL REQUIREMENTS AND INFORMATION

ELEC RISER - TRANSFORMER SCHEDULE

NAME	SIZE	MOUNT	PRIMARY VOLTAGE	SECONDARY VOLTAGE	PRIMARY DISCONNECT	SECONDARY DISCONNECT
T-1C-NL2C	75 KVA	FLOOR	480V	208V	PANEL MCB	DISCONNECT SWITCH
T-1C-NL3C	75 KVA	FLOOR	480V	208V	PANEL MCB	PANEL CIRCUIT BREAKER

REFER TO "POWER DISTRIBUTION RISER DIAGRAM" ON SHEET ES601 FOR ADDITIONAL REQUIREMENTS AND INFORMATION



POWER INTERRUPTION NOTE :

TWO WEEKS (MINIMUM NOTICE) PRIOR TO ANY INTERRUPTION OF HOSPITAL POWER, CONTRACTOR SHALL COORDINATE ALL EXPECTED PROCEDURES WITH HOSPITAL ENGINEER / STAFF. ALSO, ONE MONTH PRIOR TO INTERRUPTING POWER, CONTRACTOR SHALL SUBMIT TO OWNER/ENGINEER A DETAILED OUTLINE AND DESCRIPTION OF HOW THIS PROCEDURE IS TO TAKE PLACE, FOR HOW LONG POWER WILL BE DOWN, WHO HAS BEEN CONTACTED, ETC. THIS OUTLINE AND DESCRIPTION IS TO BE SUBMITTED AS SHOP DRAWINGS TO THE ENGINEER FOR REVIEW. NO INTERRUPTION OF MAIN SERVICE POWER SHALL OCCUR WITHOUT THE ENGINEER'S WRITTEN APPROVAL OF THE ABOVE REFERENCED MATERIAL.

TEMPORARY AHU UNIT TO BE SERVED FROM NEW CIRCUIT BREAKER INDICATED. ONCE INSTALLATION OF NEW 1-AHU-2 IS COMPLETE, BREAKER WILL BE DISCONNECTED FROM TEMPORARY AHU UNIT AND SHALL SERVE NEW 1-AHU-2. COORDINATE EXACT PHASING WITH OWNER PRIOR TO CONSTRUCTION. CONTRACTOR TO PROVIDE OWNER WITH COMPLETE PHASING AND INSTALLATION SCHEDULE SO AS TO AVOID UNIT DOWNTOWN AS MUCH AS POSSIBLE.

POWER DISTRIBUTION RISER DIAGRAM
NO SCALE

Revisions:	Date:

CONSULTANT

Consultant:
 CMTA CONSULTING ENGINEERS, INC
 10411 MEETING STREET
 PROSPECT, KY 40059

ARCHITECT/ENGINEER OF RECORD

A/E:
 GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388

STAMP

Office of Construction and Facilities Management

Drawing Title
POWER DISTRIBUTION RISER DIAGRAM AND DETAILS

Phase
BID DOCUMENTS

Approved:

Project Title
VA WICHITA - MED SURG BEDS FOR PATIENT PRIVACY

Location
WICHITA, KANSAS

Issue Date
 05/22/2020

Checked
 PDY


Drawn
 RAH

Project Number
589-701

Building Number
1 & 1C


Drawing Number
ES601

V:\Projects\VKMR19\8_Elec\1_Drawings\VKMR19_ES601.dwg-Work May 21, 2020-5:40pm - mleppng




GENERAL TROFFER SUPPORT DETAIL NOTES:
 1. SUPPORT WIRES SHALL BE GALVANIZED REGULAR COATING, SOFT TEMPER, 0.1055 INCHES IN DIAMETER (12 GAUGE).
 2. ALTERNATELY, CONTRACTOR MAY SUPPORT FIXTURES WITH SINGLE WIRE FROM ALL FOUR CORNERS OF FIXTURE PER SPECIFICATIONS WITH NUMBER OF TWISTS AT FIXTURE AND NUMBER OF WRAPS AROUND STRUCTURE INDICATED IN THIS DETAIL.

3 TROFFER SUPPORT DETAIL
 SCALE: NONE



NOTES:
 A. COORDINATE ABOVE CEILING WORK WITH ALL TRADES TO ENSURE COMPONENTS ABOVE CEILING REQUIRING ACCESS ARE INSTALLED IN SUCH A WAY THAT THEY CAN BE ACCESSED THROUGH FIXTURE OPENING.
 B. COMPLETE INSTALLATION SHALL BE PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.

2 FIXTURE ACCESS IN DRYWALL CEILING DETAIL
 SCALE: NONE





NOTES:
 • PROVIDE LED STRIPS WITH ALL 24V FITTINGS REQUIRED.
 • LOW VOLTAGE POWER SUPPLY SHALL REQUIRE 277V HARDWIRED CONNECTION.
 • PROVIDE LINE VOLTAGE WALL SWITCH FOR ALL ROOMS WITH TYPE "UC" LIGHTING. SWITCH SHALL CONTROL ALL TYPE "UC" LIGHTS IN ROOM.
 • CONNECT TYPE "UC" LIGHTING TO 277V NORMAL POWER LIGHTING CIRCUIT IF PRESENT IN ROOM. OTHERWISE CONNECT TO 277V EMERGENCY POWER LIGHTING CIRCUIT IN ROOM.

4 LIGHT FIXTURE TYPE "UC" INSTALLATION DETAIL
 SCALE: NONE

ELEC - LUMINAIRE SCHEDULE

TYPE	Count	DESCRIPTION	BASIS OF DESIGN	EQUALS	CCT	DELIVERED LUMENS	MAXIMUM WATTAGE	VOLTAGE	REMARKS
A1	100	2X4 LED FLAT PANEL, LOW OUTPUT	METALUX #24CZ-LD5-35-S-L835-HCD-1-U	LITHONIA EQUAL, APPROVED EQUAL	LED/3500K	3500 LUMENS	25	120	
A1F	2	2X4 LED FLAT PANEL, LOW OUTPUT, WITH DRYWALL FRAME KIT	METALUX #24FPX-31-L835-GL-HCD-DF-24W-U-DF-24-W	LITHONIA EQUAL, APPROVED EQUAL	LED/3500K	3500 LUMENS	25	120	
A2	1	2X4 LED FLAT PANEL, MEDIUM OUTPUT	METALUX #24CZ-LD5-45-S-L835-HCD-1-U	LITHONIA EQUAL, APPROVED EQUAL	LED/3500K	4500 LUMENS	36	120	
A3	7	2X4 LED FLAT PANEL, HIGH OUTPUT	METALUX #24CZ-LD5-60-S-L835-HCD-1-U	LITHONIA EQUAL, APPROVED EQUAL	LED/3500K	6000 LUMENS	52	120	
B1	69	2X2 LED FLAT PANEL, LOW OUTPUT	METALUX #22CZ-LD5-34-S-L835-HCD-1-U	LITHONIA EQUAL, APPROVED EQUAL	LED/3500K	3560 LUMENS	31	120	
B2	10	2X2 DECORATIVE PANEL, HIGH OUTPUT	VISA LIGHTING #CM1938-L35K-H-90CRI-XXX	APPROVED EQUAL	LED/3500K	5900 LUMENS	72	120	
D3-10	20	3" RECESSED ADJUSTABLE LED CAN LIGHT	LUMENPULSE #LACS-B-L13-35K-CR80-N-RD-WH-DA1	APPROVED EQUAL	LED/3500K	1000 LUMENS	37	120	ARCHITECT TO SELECT FINAL FINISH PRIOR TO ORDERING. CONFIRM ACTUAL CEILING TYPES AND INSTALLATION REQUIREMENTS WITH ARCHITECT'S FINAL CEILING PLANS PRIOR TO ORDERING OF MATERIALS. PROVIDE ALL MOUNTING HARDWARE AND ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.
D4-15	23	4" RECESSED LED CAN LIGHT	PORTFOLIO #LD4B-15-D010-EU4B-1020-835-4LBM-1H	APPROVED EQUAL	LED/3500K	1500 LUMENS	16	120	ARCHITECT TO SELECT FINAL FINISH PRIOR TO ORDERING. CONFIRM ACTUAL CEILING TYPES AND INSTALLATION REQUIREMENTS WITH ARCHITECT'S FINAL CEILING PLANS PRIOR TO ORDERING OF MATERIALS. PROVIDE ALL MOUNTING HARDWARE AND ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.
D6-20	75	6" RECESSED LED CAN LIGHT	PORTFOLIO #LD6B-20-D010-EU6B-1020-835-6LBM-1H	APPROVED EQUAL	LED/3500K	2000 LUMENS	21	120	ARCHITECT TO SELECT FINAL FINISH PRIOR TO ORDERING. CONFIRM ACTUAL CEILING TYPES AND INSTALLATION REQUIREMENTS WITH ARCHITECT'S FINAL CEILING PLANS PRIOR TO ORDERING OF MATERIALS. PROVIDE ALL MOUNTING HARDWARE AND ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.
DS-15	11	6" RECESSED SHALLOW LENS LED SHOWER CAN LIGHT	HALO PD6-15-D010-PDM6A-835-64V-H	APPROVED EQUAL	LED/3500K	1500 LUMENS	15	120	ARCHITECT TO SELECT FINAL FINISH PRIOR TO ORDERING. CONFIRM ACTUAL CEILING TYPES AND INSTALLATION REQUIREMENTS WITH ARCHITECT'S FINAL CEILING PLANS PRIOR TO ORDERING OF MATERIALS. PROVIDE ALL MOUNTING HARDWARE AND ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.
F1	20	4FT LED ROUND STRIP FIXTURE WITH LENS	WILLIAMS #75R-4-L50-835-DRV	METALUX EQUAL, APPROVED EQUAL	LED/3500K	4214 LUMENS	35	120	
F2	1	2FT LED ROUND STRIP FIXTURE WITH LENS	WILLIAMS #75R-2-L50-835-DRV	METALUX EQUAL, APPROVED EQUAL	LED/3500K	2162 LUMENS	18	120	
ST	21	RECESSED AMBER NIGHT LIGHT	FAIL-SAFE #MSN-UNV-W	APPROVED EQUAL	LED/3500K	AMBER LIGHTS 30 LUMENS MINIMUM	5	120	
TL	4	LED TAPE LIGHT	JESCO #XX-DL-FLEX2-SHO-3590	APPROVED EQUAL	LED	1128 LUMENS/FT	9	120	
U1	18	18" LED UNDERCABINET FIXTURE	HALO #HU30-BSC-18-P	APPROVED EQUAL	LED/3500K	440 LUMENS	8	120	SPECIFY EXACT LENGTHS PRIOR TO ORDERING OF MATERIALS. PROVIDE LINEAR MOUNTING CHANNELS AS REQUIRED. REFER TO ARCHITECT'S DETAILS AND SECTION VIEWS FOR ADDITIONAL REQUIREMENTS AND INFORMATION. PROVIDE REMOTE DIMMING DRIVER. CONSULT MANUFACTURER.
U2	21	24" LED UNDERCABINET FIXTURE	HALO #HU30-BSC-24-P	APPROVED EQUAL	LED/3500K	627 LUMENS	11	120	
V1	12	LED WALL MOUNT VAINITY FIXTURE	VISA LIGHTING #CB5513-L35K-H-GSIL	APPROVED EQUAL	LED/3500K	1500 LUMENS	15	120	ARCHITECT TO SELECT FINAL FINISH PRIOR TO ORDERING.
W1	1	LED WALL MOUNT ROOF TOP FIXTURE	LITHONIA #TW2R2-LED-P1-40K-PE-DOBTKD	APPROVED EQUAL	LED/4000K	8000 LUMENS	64	120	PROVIDE WITH INTEGRAL PHOTOCELL FOR AUTOMATIC DUSK/DAWN OPERATION.
X1	16	UNIVERSAL MOUNT LED EXIT SIGN	LITHONIA #EDGR-W-X-R-WM	APPROVED EQUAL	LED		2	120	PROVIDE ARROWS AND MOUNTING ACCESSORIES AS REQUIRED FOR INSTALLATION. MATCH ARROWS WITH ARCHITECT'S PATH OF EGRESS PLAN. REFER TO FLOOR PLANS FOR LOCATIONS, MOUNTING, AND QUANTITIES. PROVIDE ALL MOUNTING HARDWARE AND ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.
X2	6	UNIVERSAL MOUNT, DOUBLE FACED, LED EXIT SIGN	LITHONIA #EDGR-W-X-R-WM	APPROVED EQUAL	LED		2	120	PROVIDE ARROWS AND MOUNTING ACCESSORIES AS REQUIRED FOR INSTALLATION. MATCH ARROWS WITH ARCHITECT'S PATH OF EGRESS PLAN. REFER TO FLOOR PLANS FOR LOCATIONS, MOUNTING, AND QUANTITIES. PROVIDE ALL MOUNTING HARDWARE AND ACCESSORIES AS REQUIRED FOR A COMPLETE INSTALLATION.

GENERAL NOTES (LUMINAIRE SCHEDULE):
 A. ALL LUMINAIRES AND COMPONENTS SHALL BE UL LISTED.
 B. WHERE LUMINAIRES ARE SHOWN SPLIT-WIRED (HALF EMERGENCY POWER/ HALF NORMAL POWER) ON FLOOR PLANS, LUMINAIRES SHALL BE PROVIDED WITH MULTIPLE ELECTRONIC BALLASTS FOR MULTIPLE POWER CIRCUITS AS INDICATED ON FLOOR PLANS.
 C. PROVIDE BALLASTS FOR FIXTURE LAMP SWITCHING AS INDICATED ON LIGHTING FLOOR PLANS. WHERE A SINGLE FIXTURE IS POWERED FROM NORMAL AND EMERGENCY POWER, HALF OF THE LAMPS WITH A MINIMUM OF TWO LAMPS SHALL BE ON EMERGENCY POWER.
 D. CONTRACTOR SHALL FOCUS, AIM AND ADJUST LUMINAIRES UNDER THE SUPERVISION AND DIRECTION OF THE ENGINEER AND ARCHITECT. ALLOW LABOR FOR FINAL FOCUS AND ADJUSTMENTS AFTER DARK. LIFTS AND SCAFFOLDING SHALL BE AVAILABLE.
 E. ALL LAY-IN FIXTURES SHALL BE PROVIDED WITH SCREW ON HOLD DOWN CLIPS AND MAXIMUM 6'-0" LONG FLEXIBLE CONDUIT WHIPS.
 F. EXIT SIGNS AND FIXTURES THAT ARE HATCHED OR WHERE THE FIXTURE TYPE CONTAINS THE SUFFIX "E" FOR EMERGENCY OPERATION SHALL HAVE AN INTEGRAL 90 MINUTE BATTERY INVERTER IF NOT POWERED FROM AN EMERGENCY GENERATOR.
 G. ALL BATTERY POWERED FIXTURES SHALL HAVE TEST SWITCHES FACTORY INSTALLED INTEGRAL TO THE REFLECTOR. REMOTE TEST SWITCHES WILL NOT BE ACCEPTED.



1 OCCUPANCY/VACANCY/DAYLIGHT SENSOR LIGHTING CONTROL WIRING DIAGRAM
 SCALE: NONE

Revisions:	Date:

CONSULTANT
 Consultant:
CMTA CONSULTING ENGINEERS, INC.
 10411 MEETING STREET,
 PROSPECT, KY 40059
 (502)326-3085

ARCHITECT/ENGINEER OF RECORD
 A/E:
GUIDON DESIGN, INC
 1221 N PENNSYLVANIA STREET
 INDIANAPOLIS, IN 46202
 (317) 800-6388

Office of Construction and Facilities Management
 VA U.S. Department of Veterans Affairs

Drawing Title
LIGHT FIXTURE SCHEDULE AND DETAILS

Phase
BID DOCUMENTS

Approved:

Project Title
VA WICHITA - MED/SURG BEDS FOR PATIENT PRIVACY

Location
WICHITA, KANSAS

Issue Date
 05/22/2020

Checked
 PDY

Drawn
 RAH

Project Number
589-701

Building Number
1 & 1C

Drawing Number
ES701

5/21/2020 5:47:59 PM C:\Users\mhp\p\p\Documents\WMT19 ELEC R18_Z_mhp\p\p\ZJR.rvt

PANELBOARD AND WIRING SCHEDULE													K&C VALUE: 22							
PANEL: 1C-NH3C													MAINS TYPE: MLO							
VOLTAGE: 480Y/277V, 3P, 4W													SPD: No							
AMPERES: 400 A													LOCATION: ELEC CLOSET C309							
MOUNTING: SURFACE													SUPPLY FROM:							
CIRCUIT DESCRIPTION	NOTE	WIRE	GND	C	OC	P	CKT	A	B	C	CKT	P	OC	C	GND	WIRE	NOTE	CIRCUIT DESCRIPTION		
1-RTU1 (RETURN FAN)					20	1	3	0.2				2	1	20				1-RTU1 (SUPPLY FAN)		
E-1-CRAC1 (ROOF)					20	3	9	4.4	2.7	4.4		10	3	20				E-1-CRAC2 (ROOF)		
E-1-CRAC3 (ROOF)					20	3	15	4.4	2.7			16	3	20				E-1-CRAC4 (ROOF)		
XFMR "1-C-NL3C"		3	8	1-1/4	100	3	39	15.0	14.6			40	3	100	1-1/4	8	3	XFMR "1-C-NL2C"		
TOTAL LOAD (kVA): 45.6 kVA													47.8 kVA		45.4 kVA					
TOTAL CURRENT (A): 166 A													174 A		157 A					
LOAD CLASSIFICATION													CONNECTED LOAD		DEMAND FACTOR		ESTIMATED DEMAND		PANEL TOTALS	
EQUIP													63500 VA		100.00%		63500 VA		TOTAL CONNECTED LOAD: 136824 VA	
LTNG													3664 VA		100.00%		3664 VA		TOTAL ESTIMATED DEMAND: 106594 VA	
REC													69650 VA		57.18%		39830 VA		TOTAL CONNECTED CURRENT: 165 A	
																	TOTAL ESTIMATED DEMAND CURRENT: 129 A			

PANELBOARD AND WIRING SCHEDULE													K&C VALUE: 22							
PANEL: 1-ELEQ3E													MAINS TYPE: MLO							
VOLTAGE: 208Y/120V, 3P, 4W													SPD: No							
AMPERES: 100 A													LOCATION: ELEC CLOSET 362							
MOUNTING: SURFACE													SUPPLY FROM:							
CIRCUIT DESCRIPTION	NOTE	WIRE	GND	C	OC	P	CKT	A	B	C	CKT	P	OC	C	GND	WIRE	NOTE	CIRCUIT DESCRIPTION		
BAS PANEL - ELEC C207					20	1	1	0.5	0.5			2	1	20				BAS PANEL - ELEC C309		
1EF-11 ATTIC					20	1	3		0.5	0.7		4	1	20				1EF-11 ATTIC		
1A-C1 DATA C310					20	1	7	1.0				6	1	20				1A-C1 DATA C208		
TOTAL LOAD (kVA): 2.0 kVA													1.2 kVA		2.3 kVA					
TOTAL CURRENT (A): 15 A													10 A		20 A					
LOAD CLASSIFICATION													CONNECTED LOAD		DEMAND FACTOR		ESTIMATED DEMAND		PANEL TOTALS	
EQUIP													5480 VA		100.00%		5480 VA		TOTAL CONNECTED LOAD: 5480 VA	
																	TOTAL ESTIMATED DEMAND: 5480 VA			
																	TOTAL CONNECTED CURRENT: 15 A			
																	TOTAL ESTIMATED DEMAND CURRENT: 15 A			

PANELBOARD AND WIRING SCHEDULE													K&C VALUE: 22							
PANEL: 1-ELLS3E													MAINS TYPE: MLO							
VOLTAGE: 208Y/120V, 3P, 4W													SPD: No							
AMPERES: 100 A													LOCATION: ELEC CLOSET 362							
MOUNTING: SURFACE													SUPPLY FROM:							
CIRCUIT DESCRIPTION	NOTE	WIRE	GND	C	OC	P	CKT	A	B	C	CKT	P	OC	C	GND	WIRE	NOTE	CIRCUIT DESCRIPTION		
1-RTU1 (RETURN FAN)					20	1	1	0.4	0.3			2	1	20				1-RTU1 (RETURN FAN)		
2ND FLOOR - DOOR...					20	1	3		0.2	0.2		4	1	20				3RD FLOOR - DOOR...		
NAC IT 243					20	1	5			0.5	0.5	6	1	20				NAC BIOMED 345		
3RD FLOOR - DOOR...					20	1	7	0.0	0.2			8	1	20				LPA - EQUIP STOR 349		
TOTAL LOAD (kVA): 0.9 kVA													0.4 kVA		1.0 kVA					
TOTAL CURRENT (A): 8 A													3 A		9 A					
LOAD CLASSIFICATION													CONNECTED LOAD		DEMAND FACTOR		ESTIMATED DEMAND		PANEL TOTALS	
EQUIP													1600 VA		100.00%		1600 VA		TOTAL CONNECTED LOAD: 2283 VA	
LTNG													683 VA		100.00%		683 VA		TOTAL ESTIMATED DEMAND: 2283 VA	
																	TOTAL CONNECTED CURRENT: 6 A			
																	TOTAL ESTIMATED DEMAND CURRENT: 6 A			

PANELBOARD AND WIRING SCHEDULE													K&C VALUE: 22							
PANEL: 1C-NL2C													MAINS TYPE: 225A/3P MCB							
VOLTAGE: 208Y/120V, 3P, 4W													SPD: No							
AMPERES: 100 A													LOCATION: ELEC C207							
MOUNTING: SURFACE													SUPPLY FROM:							
CIRCUIT DESCRIPTION	NOTE	WIRE	GND	C	OC	P	CKT	A	B	C	CKT	P	OC	C	GND	WIRE	NOTE	CIRCUIT DESCRIPTION		
REC - RT SHARED C202					20	1	1	1.8	0.4			2	1	20				LTNG - CORR C201		
REC - RT SHARED C202					20	1	3		1.1	0.6		4	1	20				LTNG - MED TEAM C205		
REC - RT OFFICE C203					20	1	5			0.7	0.8	6	1	20				LTNG - OFFICE C206		
REC - MED TEAM C204					20	1	7	1.1	0.7			8	1	20				REC - MED TEAM C205		
REC - MED TEAM C204					20	1	9		1.1	0.7		10	1	20				REC - MED TEAM C206		
REC - MED TEAM C204					20	1	11			1.4	0.4	12	1	20				REC - CORR 3-2		
REC - MED TEAM C204					20	1	13	1.6	0.7			14	1	20				REC - CORR 3-3		
REC - MED TEAM C204					20	1	15		1.1	0.7		16	1	20				REC - MED TEAM C204		
REC - MED TEAM C204					20	1	17			1.1	0.5	18	1	20				REC - RT EQUIP STOR C210		
REC - MED TEAM C204					20	1	19	0.2	0.5			20	1	20				REC - RT EQUIP STOR C210		
REC - MED TEAM C204					20	1	21		0.2	0.9		22	1	20				REC - MANAGER C217		
REC - MED TEAM C205					20	1	23		1.1	1.3		24	1	20				REC - OAA C217		
REC - MED TEAM C205					20	1	25	1.4	0.2			26	1	20				REC - PANTRY 241		
REC - MED TEAM C205					20	1	27			1.4	0.2	28	1	20				ICE MACHINE - PANTRY 241		
REC - MED TEAM C205					20	1	29			1.8	0.2	30	1	20				FRIDGE - PANTRY 241		
REC - MED TEAM C205					20	1	31	0.2	0.5			32	1	20				REC - CONSULT 242		
MICROWAVE - TEAM C204					20	1	33		0.2	0.2		34	1	20				MICROWAVE - STAFF 228		
MICROWAVE - TEAM C209					20	1	35		0.9	0.2		36	1	20				COFFEE - STAFF 228		
SPACE					20	1	37	0.0	0.0			38	1	20				SPACE		
SPACE					20	1	39			0.0	0.0	40	1	20				SPACE		
REC - OFFICE C206					20	1	43	1.4	0.2			44	1	20				REC - TOILET/SHWR C215A		
REC - OFFICE C206					20	1	45		1.1	1.3		46	1	20				REC - NOCTURNIST C215		
REC - DAYTURNIST C214					20	1	47		1.4	1.4		48	1	20				REC - DAYTURNIST C214		
REC - ICU NURSE MGR C212					20	1	49	1.6	0.9			50	1	20				REC - STAFF FLT 228B		
REC - RT EQUIP STOR C210					20	1	51		0.5	1.1		52	1	20				REC - HSPR 229		
REC - RT EQUIP STOR C210					20	1	53		0.5	1.6	0.4	54	1	20				REC - OFFICE ICU C213		
REC - STORAGE C219A					20	1	55	0.5	0.2			56	1	20				COFFEE - PANTRY 342		
REC - STORAGE C219A					20	1	57		0.8	0.5		58	1	20				REC - RT EQUIP STOR C210		
ROOF RECEPTACLES &...					20	1	59			0.2	0.0	60	1	20				REC - ELEC CLOSET 362		
					20	1	61					62	1	20				VENDING - LOUNGE 240		
TV-A IT 243					20	1	63		0.5	0.5		64	1	20				AMP IT 243		
PA-A BIOMED 243					20	1	65			0.5		66	1	20						
					20	1	67					68	1	20						
					20	1	69					70	1	20						
					20	1	71					72	1	20						
SPACE					20	1	73	0.0	0.0			74	1	20				SPACE		
SPACE					20	1	75		0.0	0.0		76	1	20				SPACE		
SPACE					20	1	77		0.0	0.0		78	1	20				SPACE		
SPACE					20	1	79	0.0	0.0			80	1	20				SPACE		
SPACE					20	1	81		0.0	0.0		82	1	20				SPACE		
SPACE					20	1	83			0.0	0.0	84	1	20				SPACE		
TOTAL LOAD (kVA): 14.3 kVA													14.6 kVA		16.0 kVA					
TOTAL CURRENT (A): 119 A													122 A		134 A					
LOAD CLASSIFICATION													CONNECTED LOAD		DEMAND FACTOR		ESTIMATED DEMAND		PANEL TOTALS	
EQUIP													2300 VA		100.00%		2300 VA		TOTAL CONNECTED LOAD: 44926 VA	
LTNG													1766 VA		100.00%		1766 VA		TOTAL ESTIMATED DEMAND: 29496 VA	
REC													40860 VA		62.24%		25430 VA		TOTAL CONNECTED CURRENT: 125 A	
																	TOTAL ESTIMATED DEMAND CURRENT: 82 A			

PANELBOARD AND WIRING SCHEDULE													K&C VALUE: 22					
PANEL: 1C-NL3C													MAINS TYPE: 225A/3P MCB					
VOLTAGE: 208Y/120V, 3P, 4W													SPD: No					
AMPERES: 225 A													LOCATION: ELEC CLOSET C309					
MOUNTING: SURFACE													SUPPLY FROM:					
CIRCUIT DESCRIPTION	NOTE	WIRE	GND	C	OC	P	CKT	A	B	C	CKT	P	OC	C	GND	WIRE	NOTE	CIRCUIT DESCRIPTION
REC - OFFICE C317					20	1	1	1.3	1.6			2	1	20				REC - OFFICE C318
REC - OFFICE C319					20	1	3		1.8	0.9		4	1	20				REC - STORAGE C308
REC - PANTRY 342					20	1	5			0.2	0.9	6	1	20				REC - DISCHARGE 343
1EF-13 (ROOF)					20	1	7	0.5	1.1			8	1	20				REC - GEN STORAGE C305
REC - PT TREATMENT C307					20	1	9		1.4	1.1		10	1	20				REC - PT TREATMENT C307
REC - PT TREATMENT C307					20	1	11			1.1	0.9	12	1	20				REC - STAFF FLT 337B
COFFEE - STAFF 337					20	1	13	0.2	0.2			14	1	20				MICROWAVE - STAFF 337
REC - OFFICE C303					20	1	15											

SECURITY ACCESS CONTROL (FACS) SYSTEM NOTES:

COORDINATE INSTALLATION OF SYSTEM WITH OWNER'S SECURITY ACCESS CONTROL VENDOR. THE CURRENT SYSTEM "ADVANTOR" IS TO BE REPLACED WITH NEW SYSTEM HEAD-END ("C-PURE 9000" BY SOFTWARE HOUSE) BEING INSTALLED ON A SEPARATE I.D. RENOVATION PROJECT. ALL NEW DEVICES ON THIS PROJECT SHALL MATCH THE NEW "C-PURE 9000" SYSTEM BEING INSTALLED. PROVIDE AND INSTALL ALL NEW SYSTEM DEVICES (INCLUDE THIS "PRICING" IN THE ELECTRICAL BID). PROVIDE ALL CABLING AND INSTALL ALL ROUGH-IN'S, POWER CONNECTIONS, ETC.

BADGE READER TYPE: 11000051 1 PROX READER KEYPAD PIV CLASS
BADGE READER SYSTEM: C-PURE 9000 BY SOFTWARE HOUSE

PROVIDE ALL EQUIPMENT, DEVICES, COMPONENTS, ALL WIRING, CONFIGURATION AND PROGRAMMING TO EXPAND THE EXISTING SYSTEMS TO ACCOMMODATE NEW DEVICES. NEW DEVICES SHALL BE SELECTED TO MATCH THE EXISTING IN CONSTRUCTION AND PERFORMANCE AND IN CONSISTENCY WITH THE EXISTING "C-PURE 9000" SYSTEM. PREPARE DRAWINGS INDICATING ALL DEVICES AND COMPONENTS TO BE ADDED INDICATING TYPE, MOUNTING HARDWARE, ZONES, ETC. ADD ADDITIONAL EQUIPMENT AS REQUIRED TO ACCOMMODATE THE NEW COMPONENTS AND DEVICES IN A MANNER CONSISTENT WITH THE CURRENT DESIGN OF THE "C-PURE 9000" SYSTEM. CURRENTLY THE CONNECTION POINT IS WITHIN THE HOSPITAL EMERGENCY DEPARTMENT (VERIFY EXACT CLOSET LOCATION PRIOR TO BID). MODIFY THE EXISTING CONSOLES AS REQUIRED TO ACCOMMODATE THE NEW DEVICES. PROVIDE ALL PROGRAMMING, BALANCING AND COMMISSIONING AS REQUIRED UP TO AND INCLUDING A COMPLETE RE-PROGRAM AND BALANCING OF THE EXISTING "C-PURE 9000" SYSTEM SO THAT ADDITION OF THE NEW DEVICES AND EQUIPMENT ARE INCORPORATED SEAMLESSLY INTO THE EXISTING HOSPITAL SYSTEMS. THE CONTRACTOR IS COMPLETELY RESPONSIBLE FOR EXAMINING SITE CONDITIONS TO DETERMINE THE EXTENT OF THE EXPANSION REQUIRED TO MEET THE ABOVE PERFORMANCE REQUIREMENTS.

TAKE DOWN ALL EXISTING "WANDERGUARD" DEVICES WITHIN RENOVATED AREAS OF THE PROJECT. PROTECT AND STORE THEM UNTIL THEY CAN BE RELOCATED TO THE RENOVATED SPACES. WIRING SPACES BE PROVIDED FROM FACS SYSTEM TO THESE RELOCATED DEVICES (LOCATE PER SYSTEM PARAMETERS AS REQUIRED). THE CONTRACTOR SHALL CONFIRM ALL DEVICE LOCATIONS (PRIOR TO ANY ROUGH-IN) WITH FACS SYSTEM COMPONENTS. PROVIDE ADDITIONAL NEW SYSTEM DEVICES (ABLE TO SEAMLESSLY INTEGRATE WITH EXISTING COMPONENTS) AS REQUIRED FOR SYSTEM OPERATION.

CONTRACTOR TO VERIFY BACKBOX SIZES AND EXACT ROUGH-IN REQUIREMENTS FOR SYSTEM WITH MANUFACTURER PRIOR TO BID.

SECURITY VIDEO SURVEILLANCE "CTCY" SYSTEM NOTES:

COORDINATE INSTALLATION OF SYSTEM WITH OWNER'S CURRENT VIDEO SURVEILLANCE VENDOR. ALL NEW DEVICES ON THIS PROJECT SHALL MATCH THE EXISTING SYSTEM. PROVIDE AND INSTALL ALL NEW SYSTEM DEVICES (INCLUDE THIS "PRICING" IN THE ELECTRICAL BID). PROVIDE ALL CABLING AND INSTALL ALL ROUGH-IN'S, POWER CONNECTIONS, ETC.

CAMERA: BOSCH FLEX DOME IP 8000
VIDEO SURVEILLANCE SYSTEM: TYCO VIDEO-EDGE

PROVIDE ALL EQUIPMENT, DEVICES, COMPONENTS, ALL WIRING, CONFIGURATION AND PROGRAMMING TO EXPAND THE EXISTING SYSTEMS TO ACCOMMODATE NEW DEVICES. NEW DEVICES SHALL BE SELECTED TO MATCH THE EXISTING IN CONSTRUCTION AND PERFORMANCE AND IN CONSISTENCY WITH THE EXISTING "TYCO" SYSTEM. PREPARE DRAWINGS INDICATING ALL DEVICES AND COMPONENTS TO BE ADDED INDICATING TYPE, MOUNTING HARDWARE, ZONES, ETC. ADD ADDITIONAL EQUIPMENT AS REQUIRED TO ACCOMMODATE THE NEW COMPONENTS AND DEVICES IN A MANNER CONSISTENT WITH THE CURRENT DESIGN OF THE "TYCO" SYSTEM. CURRENTLY THE CONNECTION POINT IS WITHIN THE POLICE STATION BUILDING-19 DISPATCH AREA (VERIFY EXACT CLOSET LOCATION PRIOR TO BID). MODIFY THE EXISTING CONSOLES AS REQUIRED TO ACCOMMODATE THE NEW DEVICES. PROVIDE ALL PROGRAMMING, BALANCING AND COMMISSIONING AS REQUIRED UP TO AND INCLUDING A COMPLETE RE-PROGRAM AND BALANCING OF THE EXISTING "TYCO" SYSTEM SO THAT THE ADDITION OF THE NEW DEVICES AND EQUIPMENT ARE INCORPORATED SEAMLESSLY INTO THE EXISTING HOSPITAL SYSTEMS. THE CONTRACTOR IS COMPLETELY RESPONSIBLE FOR EXAMINING SITE CONDITIONS TO DETERMINE THE EXTENT OF THE EXPANSION REQUIRED TO MEET THE ABOVE PERFORMANCE REQUIREMENTS.

CONTRACTOR TO VERIFY BACKBOX SIZES AND EXACT ROUGH-IN REQUIREMENTS FOR SYSTEM WITH MANUFACTURER PRIOR TO BID.


NURSE CALL SYSTEM NOTES:

COORDINATE INSTALLATION OF GE ASCOM TELLEGENE SYSTEM WITH OWNER'S VENDOR "ECC". CONTACT ELECTRONIC CONTRACTING COMPANY ("ECC") AT 316-265-7878. "ECC" TO PROVIDE AND INSTALL ALL DEVICES (INCLUDE THIS "PRICING" IN THE ELECTRICAL BID). "ECC" TO PROVIDE ALL CABLING FOR "ECC" TO INSTALL. "ECC" TO INSTALL ALL ROUGH-IN'S, POWER CONNECTIONS, ETC. CODE BLUE ANNUNCIATION SHALL BE EXTENDED TO "PBX" AS REQUIRED. MODIFY THE EXISTING COMPONENT CABINETS AS REQUIRED TO ACCOMMODATE THE NEW DEVICES. PROVIDE ALL PROGRAMMING, BALANCING AND COMMISSIONING AS REQUIRED UP TO AND INCLUDING A COMPLETE RE-PROGRAM AND BALANCING OF THE EXISTING SYSTEM SO THAT THE ADDITION OF THE NEW DEVICES AND EQUIPMENT ARE INCORPORATED SEAMLESSLY INTO THE EXISTING HEAD-END EQUIPMENT LOCATED IN BUILDING 19 ON THE GROUND FLOOR LEVEL (FIELD VERIFY BEST CABLING IN CONDUIT INTERCONNECT ROUTE PRIOR TO BID). THE CONTRACTOR IS COMPLETELY RESPONSIBLE FOR EXAMINING SITE CONDITIONS TO DETERMINE THE EXTENT OF THE EXPANSION REQUIRED TO MEET THE ABOVE PERFORMANCE REQUIREMENTS.

CONTRACTOR TO VERIFY BACKBOX SIZES AND EXACT ROUGH-IN REQUIREMENTS FOR NURSE CALL RAILLAND RESPONDER V SYSTEM WITH NURSE CALL SYSTEM MANUFACTURER PRIOR TO BID.

LOCAL PAGING SYSTEM NOTES:

PROVIDE ALL EQUIPMENT, SPEAKERS, COMPONENTS, ALL WIRING, CONFIGURATION AND PROGRAMMING TO EXPAND THE EXISTING PAGING SYSTEM TO ACCOMMODATE NEW AND RELOCATED SPEAKERS. UTILIZE AND RELOCATE EXISTING SPEAKERS WHERE POSSIBLE. NEW SPEAKERS SHALL BE SELECTED TO MATCH THE EXISTING IN CONSTRUCTION AND PERFORMANCE AND IN CONSISTENCY WITH THE EXISTING SPEAKERS AND AREAS (CONTACT JASON AT SHELLEY ELECTRIC 316-545-8311 FOR PREFERRED HOSPITAL SPEAKER TO USE). PREPARE DRAWINGS INDICATING ALL SPEAKERS TO BE ADDED OR RELOCATED, INDICATING TYPE, MOUNTING HARDWARE, CIRCUITING ZONE AND SUB-ZONE. ADD ADDITIONAL MATRIX SWITCHERS, AMPLIFIERS, CIRCUIT MONITORS AND OTHER EQUIPMENT AS REQUIRED TO ACCOMMODATE THE ADDITIONAL SPEAKERS AND ZONES IN A MANNER CONSISTENT WITH THE CURRENT DESIGN OF THE PAGING SYSTEM. MODIFY THE EXISTING CONSOLES AS REQUIRED TO ACCOMMODATE THE NEW SPEAKER ZONES. PROVIDE ALL PROGRAMMING, BALANCING AND COMMISSIONING AS REQUIRED UP TO AND INCLUDING A COMPLETE RE-PROGRAM AND BALANCING OF THE EXISTING PAGING SYSTEM SO THAT THE ADDITION OF THE NEW SPEAKERS AND EQUIPMENT ARE INCORPORATED SEAMLESSLY INTO THE EXISTING HOSPITAL PAGING SYSTEM. THE CONTRACTOR IS COMPLETELY RESPONSIBLE FOR EXAMINING SITE CONDITIONS TO DETERMINE THE EXTENT OF THE EXPANSION REQUIRED TO MEET THE ABOVE PERFORMANCE REQUIREMENTS.



DATA/VOICE SYSTEM SCHEMATIC LAYOUT OF WIRING CLOSETS - PLAN VIEW

NO SCALE


DATA/VOICE SYSTEM NOTES:

- A. REFER TO SPECIFICATIONS FOR DATA-VOICE FACEPLATE AND DEVICE REQUIREMENTS.
- B. ROUTE DATA/VOICE CABLES FROM OUTLETS SHOWN ON FLOOR PLANS TO THE NEW DATA/VOICE WIRING CLOSETS (2ND FLOOR: C208; 3RD FLOOR: C310) SHOWN ON THE ELECTRICAL SYSTEMS FLOOR PLANS. CONTRACTOR SHALL INSURE ALL RINGS SHALL BE NO GREATER THAN 300".
- C. REFER TO THE SPECIFICATIONS FOR DATA-VOICE CABLE REQUIREMENTS. ROUTE CABLING WITHIN THE CONDUIT SUB-OUT TO THE CORRIDOR CABLING PATH AND BACK TO THE NEW DATA/VOICE WIRING CLOSETS (2ND FLOOR: C208; 3RD FLOOR: C310) SHOWN ON THE ELECTRICAL SYSTEMS FLOOR PLANS. PROVIDE ADDITIONAL CABLING PATHS AS REQUIRED FOR ROUTE BACK TO THE EXISTING COMMA CLOSET WITHIN BUILDING 19 (GROUND FLOOR).
- D. PROVIDE ADDITIONAL PATCH PANELS TERMINAL BLOCKS WITH ALL NECESSARY GROUND KITS, RACK MOUNTING HARDWARE AND LABELING PER SPECIFICATION REQUIREMENTS AS REQUIRED TO ACCOMMODATE NEW CABLING BACK AT EXISTING DATA CLOSET. PROVIDE NEW VERTICAL DISTRIBUTION AND TRAY ASSEMBLIES AS NECESSARY FOR NEW CABLING AT NEW / EXISTING DATA CLOSET PER SPECIFICATION REQUIREMENTS.
- E. PANDUIT OR AMP COMPANY PRODUCTS SHALL BE USED FOR PUNCH-DOWN BLOCKS, PATCH PANELS, CONNECTORS, ETC. - NO SUBSTITUTIONS, EXCEPT IF NOT AVAILABLE AT TIME OF CONSTRUCTION. PROVIDE NUMBER OF PUNCH BLOCKS AS REQUIRED FOR PROJECT. REFER TO SPECIFICATIONS.
- F. CONTRACTOR SHALL PROVIDE (2) FULL SIZE SETS OF "TECHNOLOGY" DRAWINGS CONTAINING ALL LABELED DATA/VOICE OUTLET LOCATIONS WITH "SOFT" COPY IN 1/8" SCALE AUTOCAD DRAWINGS TO BE GIVEN TO OWNER.
- G. CONTRACTOR TO TAKE DOWN ALL EXISTING DATA "WIRELESS ACCESS POINTS" (WAPs) AS INDICATED AND STORE/PROTECT DURING CONSTRUCTION. PLACE BACK INTO NEW CEILING AT THE SAME APPROXIMATE LOCATION ONCE CEILING INSTALLATION IS COMPLETED (CLEAN UNITS PRIOR TO REINSTALLATION). NEW WIRING SHALL BE PROVIDED TO RELOCATED DEVICES AS REQUIRED. THE CONTRACTOR SHALL RE-VERIFY SYSTEM FOR THE AFFECTED AREA ONCE INSTALLATION IS COMPLETED. PROVIDE ADDITIONAL "WAP" DEVICES (MATCH EXISTING) IF REQUIRED FOR RE-CERTIFICATION.

PHILLIPS TELEMETRY SYSTEM NOTES:


TAKE DOWN EXISTING DATA "PHILLIPS TELEMETRY ANTENNAS" FROM SUSPENDED CEILING BEING REMOVED IN RENOVATED AREAS OF THE PROJECT AND TIE-OFF AT THE PRESENT LOCATION. CONTRACTOR SHALL PROTECT AND LEAVE THESE TELEMETRY ANTENNAS IN PLACE, SO AS NOT TO COMPROMISE EXISTING COVERAGE. PLACE BACK INTO NEW CEILING AT THE SAME APPROXIMATE LOCATION ONCE CEILING INSTALLATION IS COMPLETED (CLEAN UNITS PRIOR TO REINSTALLATION). NEW WIRING SHALL BE PROVIDED FROM EXISTING PHILLIPS TELEMETRY RACK (AT EQUIPMENT STORAGE 349) TO RELOCATED DEVICES AS REQUIRED. THE CONTRACTOR SHALL CONFIRM ALL DEVICE LOCATIONS (PRIOR TO ANY ROUGH-IN) WITH HOSPITAL'S SYSTEM VENDOR (PHILLIPS). CONTRACTOR TO VERIFY WITH PHILLIPS IF ANY NEW DATA DROP CABLES NEED TO BE ROUTED TO THE TELEMETRY RACK (AT EQUIPMENT STORAGE 349) INSTEAD OF TO THE NEW DATA RACKS AT DATA C208 / DATA C310. PROVIDE ADDITIONAL SYSTEM DEVICES (MATCH EXISTING) FOLLOWING VENDOR CONFIRMATION.

CONTRACTOR TO VERIFY BACKBOX SIZES AND EXACT ROUGH-IN REQUIREMENTS FOR WITH HOSPITAL'S SYSTEM VENDOR PHILLIPS PRIOR TO BID.



DATA/VOICE SYSTEM SCHEMATIC LAYOUT OF WIRING CLOSETS - ELEVATION VIEWS


NO SCALE



DATA ROOM GROUND BUS BAR DETAIL

NO SCALE

- +ALL CONDUCTORS MUST BE STRANDED, INSULATED GREEN, COPPER CONDUCTORS AND SECURED AT NO MORE THAN 3'-0" INTERVALS.
- +ALL GROUNDING CONDUCTORS AND BUS BARS MUST BE LABELED PER ANSI/TIA 606 ADDENDUMS.



DETAIL OF TYPICAL WALLPLATE TYPES FOR VOICE/DATA SYSTEMS

NO SCALE

V:\Projects\VKMR19\8_Elec\1_Drawings\VKMR19_8_Elec\1_ESS01.dwg-Work May 21, 2020-5:40pm - mleppling

Revisions:	Date:

CONSULTANT

Consultant:
CMTA CONSULTING ENGINEERS, INC
10411 MEETING STREET
PROSPECT, KY 40059

ARCHITECT/ENGINEER OF RECORD

A/E:
GUIDON DESIGN, INC
1221 N PENNSYLVANIA STREET
INDIANAPOLIS, IN 46202
(317) 800-6388

STAMP

Office of
Construction
and Facilities
Management


U.S. Department
of Veterans
Affairs

Drawing Title
**TELECOMMUNICATION
DETAILS**

Approved:

Phase
BID DOCUMENTS

Project Title VA WICHITA - MED SURG BEDS FOR PATIENT PRIVACY	Project Number 589-701
Location WICHITA, KANSAS	Building Number 1 & 1C
Issue Date 05/22/2020	Checked PDY
Drawn RAH	Drawing Number ES801



FIRE ALARM RISER DIAGRAM



NO SCALE

GENERAL F.A. SYSTEM RISER NOTES :

- THIS RISER IS PARTIAL. ALL THE DEVICES CONNECTED TO THE "CDT" UNITS ARE NOT SHOWN. THE CONTRACTOR SHALL REFER TO THE ELECTRICAL FLOOR PLANS FOR THE COMPLETE F.A. SYSTEM.
- FIELD VERIFY THE EXACT NUMBER AND LOCATIONS OF ALL MECHANICALLY RELATED ITEMS (EX. SPRINKLER CONNECTIONS, EXTINGUISHING SYSTEMS, SMOKE DAMPERS, ETC.) AND MAKE CONNECTIONS AS REQUIRED/INDICATED.
- PROVIDE CONNECTIONS TO ALL FIRE PROTECTION TAMPER AND FLOW SWITCHES (VIA "MONITOR ZAMS"). CONTRACTOR SHALL VERIFY ALL LOCATIONS WITH FIRE PROTECTION SHOP DRAWINGS. CONTRACTOR SHALL PROVIDE A UNIT PRICE FOR COMPLETE INSTALLATION OF A CONNECTION TO EXISTING FIRE PROTECTION SWITCHES.
- ALL FIRE ALARM STROBE LIGHTS SHALL BE SYNCHRONIZED TO ACCOMMODATE BUILDING STANDARDS AS REQUIRED.
- NO SMOKE DETECTOR SHALL BE LOCATED CLOSER THAN 36" TO SUPPLY, RETURN OR EXHAUST AIR OPENINGS. NOR CLOSER THAN 12" TO WALL / CEILING INTERSECTIONS.
- A TECHNICAL REPRESENTATIVE OF FIRE ALARM MANUFACTURER SHALL BE PRESENT AT ALL TIMES DURING FIRE ALARM CERTIFICATION.
- WRITTEN CERTIFICATION OF ENTIRE FIRE ALARM SYSTEM SHALL BE SUBMITTED TO OWNER & ENGINEER AT CLOSE OF PROJECT.
- ALL FIRE ALARM CABLING SHALL BE RAN COMPLETELY IN CONDUIT.
- AIR HANDLING UNITS SHALL ONLY SHUT DOWN WHEN SMOKE IS DETECTED AT THAT PARTICULAR AIR HANDLING UNIT (I.O.N.). SMOKE DAMPERS SHALL CLOSE ONLY WHEN SMOKE IS DETECTED AT THAT PARTICULAR SMOKE DAMPER BY ACTIVATION OF THE CONTROLLING SMOKE DETECTOR. REFER TO THE SPECIFICATIONS FOR FURTHER REQUIREMENTS.
- RISER DIAGRAM IS FOR BID PURPOSES ONLY. SYSTEM SHALL BE INSTALLED AND CONNECTED IN ACCORDANCE WITH WIRING DIAGRAMS OBTAINED FROM MANUFACTURER, THAT HAVE BEEN APPROVED BY THE STATE FIRE MARSHAL'S OFFICE, ETC.
- DESCRIPTIVE ENTRIES FOR LOCATION OF FIRE ALARM DEVICES ARE TO BE TURNED OVER TO FIRE ALARM MANUFACTURER AS SOON AS POSSIBLE AFTER AWARD OF CONTRACT FOR RE-PROGRAMMING OF FIRE ALARM SYSTEM. COORDINATE WITH HOSPITAL ENGINEER FOR DESCRIPTIVE ENTRY DESIGNATIONS.
- CONTRACTOR TO PROVIDE A TEST OF THE EXISTING FIRE ALARM SYSTEM (PRIOR TO DEMOLITION) IN THE AREAS OF CONSTRUCTION AND OF THOSE ZONES THAT WILL BE EXTENDED INTO THE NEW ADDITION TO VERIFY THAT ALL CABLING AND DEVICES ARE IN WORKING ORDER AND THAT THERE ARE NO WIRING FAULTS WITHIN THE SYSTEM.
- CONTRACTOR TO UTILIZE THE SERVICES OF THE MAINTENANCE CONTRACTOR (PRESENTLY WORKING AT FACILITY ON OTHER CONSTRUCTION PROJECTS) FOR ALL FIRE ALARM SYSTEM MODIFICATIONS (DEMOLITION AND TERMINATION AT NEW DEVICES, PROGRAMMING REVISIONS, ETC.). CONTRACTOR MUST ENGAGE THE SERVICES OF THE MAINTENANCE CONTRACTOR AS PART OF THE PROJECT SCOPE. COORDINATE CONTACT INFORMATION WITH COR.



FIRE ALARM RISER TAGGED NOTES :

- EXISTING NOTIFIER "CDT" (COMMUNICATING DEVICE TRANSPONDER) AS PART OF THIS CONTRACT, THIS CONTRACTOR SHALL MODIFY THE EXISTING SYSTEM COMPONENTS AS REQUIRED TO UPDATE THE EXISTING "MULTI-PLEX" FIRE ALARM SYSTEM FOR THE RENOVATED AREA AS REQUIRED.
- PROVIDE MONITOR "ZAM's" (ZONE ADAPTER MODULES) FOR ADDRESSABLE SUPERVISION OF FIRE PROTECTION VALVES. MONITOR "ZAM's" SHALL BE SURFACE MOUNTED, IN A NEMA-1 ENCLOSURE, ABOVE SUSPENDED CEILING, AS REQUIRED.
- PROVIDE CONNECTION TO AUTO / ELECTRIC STRIKE DOORS TO PROVIDE POSITIVE LATCHING UNDER ALARM CONDITIONS WITH MONITOR / CONTROL MODULE UNIT(S) IN A NEMA-1 ENCLOSURE AS REQUIRED. CONTRACTOR SHALL REFER TO ARCHITECTURAL DOOR SCHEDULES FOR EXACT LOCATION AND REQUIREMENTS. TYPICAL.
- NEW SMOKE DETECTORS ON EITHER SIDE OF SMOKE CONTROL DOORS SHALL BE PROVIDED WITH A "RELAY BASE" (OR SEPARATE INTELLIGENT INTERFACE MODULE) THAT SHALL BE WIRED TO INDIVIDUALLY CONTROL EACH OF THE MAGNETIC HOLD OPENS, SO THAT NO OTHER ALARM SHALL ACTIVATE THE HOLD OPEN DEVICES. THIS DOOR HOLD-OPEN SMOKE DETECTOR SHALL ALSO SIMULTANEOUSLY ACTIVATE A "FULL" BUILDING WIDE FIRE ALARM TO THE FIRE ALARM SYSTEM AS SPECIFIED (TYPICAL).
- PROVIDE NEW "NAC" (NOTIFICATION APPLIANCE CIRCUIT) POWER SUPPLY CABINET (NOTIFIER OR EQUAL) AS REQUIRED FOR ADDITIONAL AUDIO-VISUAL DEVICES BEING ADDED FOR THE PROJECT.
- TO OTHER SMOKE DAMPER LOCATIONS ALONG A PARTICULAR SMOKE WALL (TYPICAL) - SEE SYSTEMS FLOOR PLANS FOR LOCATIONS.
- WHERE H.V.A.C. SMOKE DAMPERS ARE LOCATED ABOVE CORRIDOR DOORS, THE CORRIDOR SMOKE DETECTOR (THE CLOSEST ONE TO THE SMOKE DAMPER) SHALL CONTROL THE SMOKE DAMPER.
- ROUTE 120V POWER WIRING THROUGH CONTROLLING DUCT SMOKE / CEILING SMOKE DETECTOR'S PROGRAMMABLE RELAY AND THEN TO THE SMOKE DAMPER AS REQUIRED. (TYPICAL).
- PROVIDE NEW FLUSH-MOUNTED REMOTE ALARM/POWER INDICATING KEY RESET/TEST STATION ON CORRIDOR WALL (WHENEVER POSSIBLE) AT 7'-0" AFF BELOW SMOKE DAMPER LOCATION AS REQUIRED.
- ROUTE CONTROL WIRING (IN CONDUIT) BACK TO NEW A.H.U. TEMPERATURE CONTROL PANEL FOR AUTOMATIC A.H.U. SHUTDOWN. THIS CONTRACTOR SHALL PROVIDE A REMOTE L.E.D. INDICATOR FOR EACH DETECTOR IF NOT SO MONITORED AT NEW A.H.U. CONTROL PANEL.




DETAIL OF CABLE TRAY PENETRATION THRU RATED WALL

NO SCALE




CABLE TRAY INSTALLATION DETAIL

NO SCALE




PANEL DEMOLITION DETAIL

NO SCALE



'J-HOOK' CABLING PATH INSTALLATION DETAIL

NO SCALE



ROUGHING-IN DETAIL FOR STUB-OUTS

NO SCALE

Revisions:	Date:

CONSULTANT

Consultant:
CMTA CONSULTING ENGINEERS, INC
10411 MEETING STREET
PROSPECT, KY 40059

ARCHITECT/ENGINEER OF RECORD

A/E:
GUIDON DESIGN, INC
1221 N PENNSYLVANIA STREET
INDIANAPOLIS, IN 46202
(317) 800-6388

STAMP

Office of
Construction
and Facilities
Management

U.S. Department
of Veterans
Affairs

Drawing Title
ELECTRICAL DETAILS

Approved:

Phase
BID DOCUMENTS

Project Title
VA WICHITA - MED SURG BEDS FOR PATIENT PRIVACY

Location
WICHITA, KANSAS

Issue Date
05/22/2020

Checked
PDY







Drawn
RAH

Project Number
589-701

Building Number
1 & 1C

Drawing Number
ES802

V:\Projects\VKMR19\8_Elec\1_Drawings\VKMR19_ES802.dwg-Work May 21, 2020-5:40pm - mleppig



Revisions:	Date:

CONSULTANT

Consultant:
CMTA CONSULTING ENGINEERS, INC
10411 MEETING STREET
PROSPECT, KY 40059

ARCHITECT/ENGINEER OF RECORD

A/E:
GUIDON DESIGN, INC
1221 N PENNSYLVANIA STREET
INDIANAPOLIS, IN 46202
(317) 800-6388

STAMP

Office of
Construction
and Facilities
Management

Drawing Title
ELECTRICAL DETAILS

Phase
BID DOCUMENTS

Approved:

Project Title
VA WICHITA - MED SURG BEDS FOR PATIENT PRIVACY

Location
WICHITA, KANSAS

Issue Date
05/22/2020

Checked
PDY

Drawn
RAH

Project Number
589-701

Building Number
1 & 1C

Drawing Number
ES803